



Torque tester

SmartCheck 400 DAPTIQ®

Product no. **96521303**
GTIN **4018754324705**
Model **SMARTCHECK 400 DAPTIQ**



Label.

Measuring r.40-400N·m Internal square 3/4"

Features.

- Industry 4.0
- bidirectional open source interface for optimal integration
- real-time transmission of stored values to the leading system
- for testing both indicating and clicking type torque wrenches
- with exchangeable square drive adaptors for square drive
- large LCD display for optimal readability
- display, display holder and main body can be rotated 180°
- compact design
- display and membrane keypad are splash-proof; the housing is made of impact-resistant plastic
- easy installation thanks to pre-fabricated holes in the mounting bracket
- variable horizontal or vertical installation
- for controlled right and left tightening test
- 3 operating modes: Continuous display of the applied torque (track), display of the torque on triggering/breaking point detection (first peak), peak value display (peak hold)
- individual entry of target torques and tolerances for evaluation of the measured value possible
- with integrated optical and acoustic overload protection
- 3 units of measurement (N·m, ft·lb, in·lb)
- micro USB interface for data export and for optional power supply
- data storage of up to 200 data sets incl. date and time stamp
- documentation software CheckMaster for transferring values and creating test certificates is available free of charge at www.stahlwille.de
- operation via supplied mains power adapter, batteries or rechargeable batteries (4 x AAA or 1 x 9V block, adapter included)
- with factory calibration certificate
- delivery in sturdy plastic case
- **display deviation ± 1%**

Advantages.

Electronic testing device for checking and adjusting indicating and triggering torque wrenches.

The real-time data transfer to the control system supports fast evaluation of the measured values and further actions.

The large LCD can be rotated 180° and is easy to read from any position.

Easy integration with leading control systems thanks to a bidirectional open source interface.

Easy documentation of the measured values on the PC via USB.



Product highlights.



PRODUCT IMAGE
IN PROGRESS

Intelligent solution for Industry 4.0.

Our SmartCheck DAPTIQ® helps with proactive test medium verification. This allows the testing device to interface seamlessly with leading control systems such as CAQ system and receive and send data in real time. Tolerance deviations can thus be detected and reported faster without interrupting ongoing processes. DAPTIQ® therefore increases safety and efficiency in production and maintenance.



Flexible mounting.

Whether mounted horizontally or vertically, the well-designed mounting points, compact design and rotatable display allow flexible positioning anywhere in the workshop.




Optimum viewing angle.

The compact testing device can be adjusted to the optimum individual viewing angle. The display can be viewed from practically anywhere, as not only the large LCD, but also the display holder and the base body can be rotated by 180°.



Communication and power supply via USB.

SmartCheck is equipped with a convenient micro-USB interface that allows stored test values to be read out and simplifies their transfer to external systems. The USB port also serves as an optional power supply for the device.



Comprehensive documentation.

The SmartCheck testing device can be easily configured with the CheckMaster software allowing direct evaluation of the measurement results. In this way, all data can be read out and saved on the PC for better monitoring and optimization of work processes.



Plug and work.

Our SmartCheck is intuitive to use and is ready for immediate use. It is space-saving and offers versatile mounting options for flexible installation. The device can be operated using a power supply or batteries and can therefore be easily positioned at any workstation, even if there is no power socket available.

Technical Attributes.

| | |
|------------------------|---------------------------|
| Measuring range N·m | 40-400 N·m |
| Internal square [inch] | 3/4 " |
| Measuring range ft·lb | 30-295 ft·lb |
| Measuring range in·lb | 354-3540 in·lb |
| Width mm (b) | 120 mm |
| Weight with box | 7036 g |
| Height mm (h) | 124 mm |
| Model no. | SmartCheck DAPTIQ® 400 |
| t | 167 mm |

Logistics data.

| | |
|-----------------------------------|---------------------------|
| Depth mm (IFS) | 395 |
| Width mm (IFS) | 315 |
| Height mm (IFS) | 145 |
| Length (packed, mm) | 395 |
| Width (packed, mm) | 315 |
| Height (packed, mm) | 145 |
| Volume (packed, dm ³) | 18.041625 dm ³ |
| Product no. | 96521303 |
| Weight (gross, kg) | 7,210 |
| Weight PAP (kg) | 0,156 |
| Weight PVC (kg) | 0,000 |
| GTIN | 4018754324705 |
| Country of origin AWR | GERMANY |
| Region of origin | Nordrhein-Westfalen |
| WEEE/ElektroG | Kleingeräte B2C |
| Customs tariff no. | 90318080 |
| Packing standard | 1 |
| Weight | 5690 g |

Parts list.



81500004
Plastic box, empty



52110063
USB mains adapter



83230103
Soft foam inserts



83230102
Soft foam inserts



91100522
Packaging material



51110057
USB cable

Variants.

| Product no. | Model no. (ERP) | Description | GTIN |
|-------------|------------------------|---|---------------|
| 96521300 | SMARTCHECK 10S DAPTIQ | Torque screwdriver testing device SmartCheck DAPTIQ® Measuring r.1-10N·m Internal square 1/4" | 4018754324675 |
| 96521301 | SMARTCHECK 10 DAPTIQ | Measuring r.1-10N·m Internal square 1/4" | 4018754324682 |
| 96521302 | SMARTCHECK 100 DAPTIQ | Measuring r.10-100N·m Internal square 3/8" | 4018754324699 |
| 96521303 | SMARTCHECK 400 DAPTIQ | Measuring r.40-400N·m Internal square 3/4" | 4018754324705 |
| 96521304 | SMARTCHECK 800 DAPTIQ | Measuring r.80-800N·m Internal square 3/4" | 4018754324712 |
| 96521305 | SMARTCHECK 1500 DAPTIQ | Measuring r.150-1500N·m Internal square 1" | 4018754334582 |

GTIN-Code.

