



## Torque tester

### SmartCheck 400 DAPTIQ®

Product no. **96521303**  
GTIN **4018754324705**  
Model **SMARTCHECK 400 DAPTIQ**



#### Label.

Measuring r.40-400N·m Internal square 3/4"

#### Features.

- Industry 4.0
- bidirectional open source interface for optimal integration
- real-time transmission of stored values to the leading system
- for testing both indicating and clicking type torque wrenches
- with exchangeable square drive adaptors for square drive
- large LCD display for optimal readability
- display, display holder and main body can be rotated 180°
- compact design
- display and membrane keypad are splash-proof; the housing is made of impact-resistant plastic
- easy installation thanks to pre-fabricated holes in the mounting bracket
- variable horizontal or vertical installation
- for controlled right and left tightening test
- 3 operating modes: Continuous display of the applied torque (track), display of the torque on triggering/breaking point detection (first peak), peak value display (peak hold)
- individual entry of target torques and tolerances for evaluation of the measured value possible
- with integrated optical and acoustic overload protection
- 3 units of measurement (N·m, ft·lb, in·lb)
- micro USB interface for data export and for optional power supply
- data storage of up to 200 data sets incl. date and time stamp
- documentation software CheckMaster for transferring values and creating test certificates is available free of charge at [www.stahlwille.de](http://www.stahlwille.de)
- operation via supplied mains power adapter, batteries or rechargeable batteries (4 x AAA or 1 x 9V block, adapter included)
- with factory calibration certificate
- delivery in sturdy plastic case
- **display deviation  $\pm 1\%$**

## Advantages.

Electronic testing device for checking and adjusting indicating and triggering torque wrenches.

The real-time data transfer to the control system supports fast evaluation of the measured values and further actions.

The large LCD can be rotated 180° and is easy to read from any position.

Easy integration with leading control systems thanks to a bidirectional open source interface.

Easy documentation of the measured values on the PC via USB.



## Product highlights.



PRODUCT IMAGE  
IN PROGRESS

### Intelligent solution for Industry 4.0.

Our SmartCheck DAPTIQ® helps with proactive test medium verification. This allows the testing device to interface seamlessly with leading control systems such as CAQ system and receive and send data in real time. Tolerance deviations can thus be detected and reported faster without interrupting ongoing processes. DAPTIQ® therefore increases safety and efficiency in production and maintenance.



### Flexible mounting.

Whether mounted horizontally or vertically, the well-designed mounting points, compact design and rotatable display allow flexible positioning anywhere in the workshop.



### Optimum viewing angle.

The compact testing device can be adjusted to the optimum individual viewing angle. The display can be viewed from practically anywhere, as not only the large LCD, but also the display holder and the base body can be rotated by 180°.



### Communication and power supply via USB.

SmartCheck is equipped with a convenient micro-USB interface that allows stored test values to be read out and simplifies their transfer to external systems. The USB port also serves as an optional power supply for the device.



### Comprehensive documentation.

The SmartCheck testing device can be easily configured with CheckMaster software, allowing direct evaluation of measurement results. This means that all data can be read out and saved on the PC for better monitoring and optimisation of the work processes.



### Plug and Work.

Our SmartCheck is intuitive and ready to use right away. It is space-saving and can be mounted flexibly with its versatile mounting options. The device is powered by either a mains power supply or batteries and can therefore be easily positioned at any workstation, even if no power outlet is available.

## Technical Attributes.

|                        |                           |
|------------------------|---------------------------|
| Measuring range N·m    | 40-400 N·m                |
| Internal square [inch] | 3/4 "                     |
| Measuring range ft·lb  | 30-295 ft·lb              |
| Measuring range in·lb  | 354-3540 in·lb            |
| Width mm (b)           | 315 mm                    |
| Height mm (h)          | 145 mm                    |
| Model no.              | SmartCheck DAPTIQ®<br>400 |
| t                      | 167 mm                    |

## Logistics data.

|                                   |                           |
|-----------------------------------|---------------------------|
| Depth mm (IFS)                    | 395                       |
| Width mm (IFS)                    | 315                       |
| Height mm (IFS)                   | 145                       |
| Length (packed, mm)               | 395                       |
| Width (packed, mm)                | 315                       |
| Height (packed, mm)               | 145                       |
| Volume (packed, dm <sup>3</sup> ) | 18.041625 dm <sup>3</sup> |
| Product no.                       | 96521303                  |
| Weight (gross, kg)                | 7,210                     |
| Weight PAP (kg)                   | 0,156                     |
| Weight PVC (kg)                   | 0,000                     |
| GTIN                              | 4018754324705             |
| Country of origin                 | GERMANY                   |
| Region of origin                  | Nordrhein-Westfalen       |
| WEEE/ElektroG                     | Kleingeräte B2C           |
| Customs tariff no.                | 90318080                  |
| Packing standard                  | 1                         |
| Weight                            | 5690 g                    |

## Variants.

| Product no. | Model no. (ERP)          | Description   | GTIN          |
|-------------|--------------------------|---|---------------|
| 96521300    | SMARTCHECK<br>10S DAPTIQ | Torque screwdriver testing device<br>SmartCheck DAPTIQ® Measuring<br>r.1-10N·m Internal square 1/4" | 4018754324675 |
| 96521301    | SMARTCHECK 10<br>DAPTIQ  | Measuring r.1-10N·m Internal square<br>1/4"   | 4018754324682 |
| 96521302    | SMARTCHECK 100<br>DAPTIQ | Measuring r.10-100N·m Internal<br>square 3/8"   | 4018754324699 |

|          |                           |   |               |
|----------|---------------------------|---|---------------|
| 96521303 | SMARTCHECK 400<br>DAPTIQ  | Measuring r.40-400N·m Internal<br>square 3/4" | 4018754324705 |
| 96521304 | SMARTCHECK 800<br>DAPTIQ  | Measuring r.80-800N·m Internal<br>square 3/4" | 4018754324712 |
| 96521305 | SMARTCHECK<br>1500 DAPTIQ | Measuring r.150-1500N·m Internal<br>square 1" | 4018754334582 |

## GTIN-Code.

