



LED penlight

13126-2



Product no. **77490012**
GTIN **4018754240579**
Model **13126-2**



Label.

LED penlight Dimensions nullmm

Properties.

- Ex-rated for zone 1
- powerful, extremely durable LEDs
- sturdy, electrically non-conductive, corrosion-resistant housing made of ABS/polycarbonate
- high impact resistance and reduced glare due to rubberised light head
- consistently bright beam for more than 80% of the life of the alkaline batteries due to eLED electronics
- rubberised front pressure switch for permanent and temporary light
- easy storage with built-in clip holder close to the lamp head
- waterproof to IP67 in water depths up to 1 m
- brightness: 40 lm
- lighting range: 67 m
- lighting time: 2.5 hours
- batteries: 2 micro-batteries AAA/LR03, alkaline, 1.5 V (not included)
- certifications: II 2G Ex ib IIB T4 Gb, II 2D Ex ib IIIC T60 °C Db, SEV 11 ATEX 0174 X

Technical attributes.

Width mm (b)	22 mm
Height mm (h)	24 mm
Length mm (L)	132 mm
Brightness	40 lm

Logistics data.

Depth mm (IFS)	135
Width mm (IFS)	28
Height mm (IFS)	23
WEEE/ElektroG	Kleingeräte B2C
Length (packaged, mm)	135
Width (packaged, mm)	28
Height (packaging, mm)	23
Volume (packaged, dm3)	0.08694 dm3
Product no.	77490012
Weight (gross, kg)	0,045

Weight PAP (kg)	0,000
Weight PVC (kg)	0,000
GTIN	4018754240579
Country of origin AWR	UNITED STATES
Region of origin	Ausländischer Ursprung
Customs tariff no.	85131000
Packing standard	1
Weight (g)	55 g

Variants.

Product no.	Model No. (ERP)	Description	GTIN
77490012	13126-2	LED penlight Dimensions nullmm	4018754240579

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal