



Double ended ring wrenches i.TCS inlay

TCS StahlwilleSTABIL® 20/10

6x7-30x32

Product no. 96830166

GTIN 4018754152094

Model StahlwilleSTABIL® TCS 20/10



Label.

Double ended ring wrenches i.TCS inlay TCS StahlwilleSTABIL® 20/10 6x7-30x32 10

Properties.

- **metric, differing** end sizes
- deeply cranked, support angle 75°
- durable, slim and lightweight design
- high flexural strength due to double-T profile
- STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
- drop-forged, hardened, and cooled in an oil bath
- Chrome Alloy Steel, chrome-plated
- safely integrated in the modular Tool Control System (TCS)

Contains 10-pieces:

10 double-ended ring wrenches **No. 20:** 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

Benefits.

High quality double-ended ring wrench, low-crank, in metric sizes.

The AS-Drive profile prevents damage to the fastener caused by force being applied to the edges of the nut or bolt.

In the modular Tool Control System (TCS) tool inlays - an intelligent storage solution for tool and workshop trolleys.

A special manufacturing process makes thin-walled rings possible - primarily for slightly lower-lying screw connections.

The distinctive STAHLWILLE rounded finish ensures the combination wrench is comfortable to hold and is easy to grip, ensuring safe working, even with oily hands.

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Order and check.

The set is securely organized in a STAHLWILLE TCS foam inlays. These durable inlays are chemical-resistant and have precise recesses for each tool. The eye-catching yellow underside of the TCS inlays serves as a signal surface to enable quick checking of the set's completeness.

Technologies and features.



Double-T profile


Our ring, open-ended and combination wrenches have an additional recess in the middle of the tool. Similar to the principle of a double-T beam, this provides a tremendous load capacity and maximum strength whilst reducing weight.



Thin-walled rings

The thin-walled diameter of our rings makes it easier to work in confined spaces. The ring wall is deeper than standard nuts, which prevents jamming.

Technical drawing.



Technical attributes.

Number of tools	10
Range	6x7-30x32

Logistics data.

Depth mm (IFS)	370
Width mm (IFS)	360

Width mm (b)	350 mm	Height mm (IFS)	60
Height mm (h)	45 mm	WEEE/ElektroG	nicht ear-pflichtig
Contents	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm	Length (packaged, mm)	370
		Width (packaged, mm)	360
		Height (packaging, mm)	90
Length mm (L)	350 mm	Volume (packaged, dm3)	11.988 dm3
Alloy	Chrome Alloy Steel	Product no.	96830166
Surface	chrome-plated	Weight (gross, kg)	2,650
Drawer dividers	2/3	Weight PAP (kg)	0,256
		Weight PVC (kg)	0,000
		GTIN	4018754152094
		Country of origin AWR	GERMANY
		Region of origin	Nordrhein-Westfalen
		Customs tariff no.	82041100
		Packing standard	1
		Weight (g)	2500 g

Parts list.



41043032
Double-ended ring
wrench



41042427
Double-ended ring
wrench



41041922
Double-ended ring
wrench



41041821
Double-ended ring
wrench



41041617
Double-ended ring
wrench



41041415
Double-ended ring
wrench



41041213
Double-ended ring
wrench



41041011
Double-ended ring
wrench



41040809
Double-ended ring
wrench



41040607
Double-ended ring
wrench

Variants.

Product no.	Model No. (ERP)	Description	GTIN
96830166	StahlwilleSTABIL® TCS 20/10	Double ended ring wrenches i.TCS inlay TCS StahlwilleSTABIL® 20/10 6x7-30x32 10	4018754152094

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal