

# Torque wrench service MANOSKOP® (N·m/ft·lb)

#### 730 Quick

Product no. 50184005

GTIN 4018754268856 Model 730/5 QUICK











Label.

Torque wrench service MANOSKOP® 730 Quick 6-50N·m 9 x 12 mm L. 315mm







## Product highlights.



#### Rapid adjustment.

Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



#### Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.



### Technologies and features.



#### QuickRelease

The QuickRelease safety lock prevents unintentional loss of insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change. In transducers: The QuickRelease safety lock helps you to quickly mount and change transducers. The transducers lock into the calibration system and only unlock again at the push of the buttons.



#### QuickSelect

Lightning-fast target value setting: Unlock the adjustment knob, set the value, and lock the knob again.



#### Low-wear bending beam system

Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that the spring does not need to be reset to '0' after use.



#### 2-component handle


Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



#### **DIN EN ISO 6789-2**

Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.

# Technical drawing.



### Technical attributes.

Scale division N·m	2 N·m
Scale division ft-lb	1 ft·lb
Measuring range N·m	6-50 N·m
Measuring range ft-lb	5-36 ft·lb
Width mm (b)	28 mm
DIN	DIN EN ISO 6789-2:2017
Size	5
Tool holder size [internal square]	9 x 12 mm
Height mm (h)	23 mm
Length mm (L)	315 mm
LF	288 mm
SF	17,5 mm

# Logistics data.

Depth mm (IFS)	315	
Width mm (IFS)	30	
Height mm (IFS)	50	
WEEE/ElektroG	nicht ear-pflichtig	
Length (packaged, mm)	350	
Width (packaged, mm)	45	
Height (packaging, mm)	45	
Volume (packaged, dm3)	0.70875 dm3	
Product no.	50184005	
Weight (gross, kg)	0,855	
Weight PAP (kg)	0,000	
Weight PVC (kg)	0,060	
GTIN	4018754268856	
Country of origin AWR	GERMANY	

Region of originNordrhein-WestfalenCustoms tariff no.82041100

Packing standard 1
Weight (g) 780 g

### Variants.

Product no.	Model No. (ERP)	Description	GTIN
50184005	730/5 QUICK	Torque wrench service MANOSKOP® 730 Quick 6-50N·m 9 x 12 mm L. 315mm	4018754268856
50184010	730/10 QUICK	Torque wrench service MANOSKOP® 730 Quick 20-100N·m 9 x 12 mm L. 370mm	4018754266203
50184012	730/12 QUICK	Torque wrench service MANOSKOP® 730 Quick 25-130N·m 14 x 18 mm L. 410mm	4018754268863
50184020	730/20 QUICK	Torque wrench service MANOSKOP® 730 Quick 40-200N·m 14 x 18 mm L. 455mm	4018754268870
50184030	730/30 QUICK	Torque wrench service MANOSKOP® 730 Quick 60-300N·m 14 x 18 mm L. 520mm	4018754324071
50184040	730/40 QUICK	Torque wrench service MANOSKOP® 730 Quick 80-400N·m 14 x 18 mm L. 590mm	4018754268887
50184065	730/65 QUICK	Torque wrench service MANOSKOP® 730 Quick 130-650N·m 14 x 18 mm L. 875mm	4018754268894
50184565	730II/65 QUICK	Torque wrench service MANOSKOP® 730 Quick 130-650N·m 22 x 28 mm L. 897mm	4018754268900

# GTIN.



### Accessories (for).





58240005 Square drive shell tool

81370002 Plastic box, empty

### Images.



