STAHLWILLE()®



Electronic workshop testing devices SENSOTORK®

7707-3W

Product no. 96521082

GTIN **4018754181155**

Model **7707N-3W**



Label.

Properties.

Electronic workshop testing device SENSOTORK® Measuring r.25-1100N·m Internal square drive 3/4"

- for testing indicating and clicking type torque wrenches
- · compact electronic testing device consisting of:
- 1 patented transducer
- 1 safety lock
- 1 display
- 1 stand with 1.5 metre cable for the display unit
- 1 spiral cable
- 1 power supply (110-230 V with interchangeable power outlet adaptors)
- 4 interchangeable square drive adaptors
- large LCD for optimum readability
- horizontal or vertical orientation
- for controlled clockwise and counter-clockwise measurements
- 3 operating modes: running display of the applied torque (Track), display of the torque on click point detection (First-Peak), peak value display (Peak-Hold)
- for clicking type torque wrenches, the actual final torque applied is also displayed, in addition to the first peak
- with QuickRelease safety lock
- not affected by transverse forces due to its particularly low-profile design
- · automatic detection of transducers
- particularly broad measurement range from about 2-100 % of the nominal value
- 3 measuring units (N·m, ft·lb, in·lb)
- software no. 7759-4, including USB adaptor and jack-push/pull cable, allows the measured values to be transmitted to a PC (no additional external power source required, power from the PC), not included, order separately (see page 51)
- when recalibrating a transducer, the test equipment remains on site and available for use with another transducer
- complies with the specifications of guideline DKD-R 10-8
- · with factory certificate
- · delivered in a sturdy plastic box
- accuracy ± 1%

Benefits.

Electronic workshop testing device for checking and adjusting indicating and setting torque wrenches.

Measurement in the large torque range up to 1,100 N·m.

Simple, quick and reliable testing of torque wrenches to ensure quality in production.

Simple changing of transducers enables quick adjustment to different measuring tasks and specific testing requirements.

The interchangeable square adaptors stored in the base allow flexible use with standard square drive sizes.



Product highlights.



Flexible mounting.

Whether mounted horizontally or vertically - the well-designed mounting points, compact design and rotatable display allow flexible positioning anywhere in the workshop.



Customised drive solution.

Up to 4 square adapters are integrated into the mounting block of the device, within easy reach, to enable flexible use with standard square drive sizes.



Adaptive measuring system.

Our SENSOTORK® 7707W features easily interchangeable transducers. This gives it the ability to be customised for individual measurement requirements.



Resistance to transverse forces.

The high level of accuracy is achieved by flat transducers and a special technology for immediate data processing directly in the transducer. Thanks to an integrated measurement amplifier, the testing device is resistant to bending moments and transverse forces.

Technologies and features.



QuickRelease


The QuickRelease safety lock helps you to quickly mount and change transducers. The sensors lock into the calibration system adaptor and only unlock again at the push of a button.




DIN EN ISO 6789-2

Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.

Technical drawing.





Technical attributes.

Logistics data.

Measuring range N·m	25-1100 N·m	Depth mm (IFS)	420
Internal square [inch]	3/4 "	Width mm (IFS)	333
Width mm (b)	180 mm	Height mm (IFS)	165

Weight with box	11000 g	WEEE/ElektroG	Kleingeräte B2C
Height mm (h1)	79 mm	Length (packaged, mm)	420
Height mm (h2)	215 mm	Width (packaged, mm)	333
Model No.	7707-3W	Height (packaging, mm)	165
t	180 mm	Volume (packaged, dm3)	23.0769 dm3
		Product no.	96521082
		Weight (gross, kg)	10,755
		Weight PAP (kg)	0,198
		Weight PVC (kg)	0,000
		GTIN	4018754181155
		Country of origin AWR	GERMANY
		Region of origin	Nordrhein-Westfalen
		Customs tariff no.	90318080
		Packing standard	1
		Weight (g)	7495 g

Parts list.



81320002 Plastic case



52110056 Mains adaptor



52110052 Spiral cable



52110051 Jack cable



52100059 Torque wrench screws



52100058 Torque wrench screws



52100051 Body mount



52100050 Display for torque display

Variants.

Product no.	Model No. (ERP)	Description	GTIN
96521086	7707-1-3W	Electronic workshop testing device SENSOTORK® Measuring r.0.2-10N·m Internal square drive 1/4"	4018754241958
96521085	7707-1-2W	Electronic workshop testing device SENSOTORK® Measuring r.0.2-10N·m Internal square drive 1/4"	4018754241941

	96521080	7707N-1W	Electronic workshop testing device SENSOTORK® Measuring r.0.4-20N⋅m Internal square drive 1/4"	4018754181148
_	96521072	7707-2W	Electronic workshop testing device SENSOTORK® Measuring r.2-100N·m Internal square drive 3/8"	4018754155781
_	96521083	7707-2-1W	Electronic workshop testing device SENSOTORK® Measuring r.4-200N·m Internal square drive 1/2"	4018754181162
_	96521084	7707-2-2W	Electronic workshop testing device SENSOTORK® Measuring r.8-400N·m Internal square drive 3/4"	4018754181179
_	96521082	7707N-3W	Electronic workshop testing device SENSOTORK® Measuring r.25-1100N·m Internal square drive 3/4"	4018754181155

GTIN.

