



Water pump pliers

6551



Product no. **65516240**
GTIN **4018754037971**
Model **6551 6 240**

Label. Water pump pliers L.240mm

Properties.

- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- Chrome Alloy Steel, forged and oil-hardened
- plastic coated handles
- DIN ISO 8976 (No. 207 C)

Benefits.

Sturdy water pump pliers for gripping, holding, pressing and bending workpieces (thin sheet metal, nuts, screws, etc.).

Sliding slip joint with double support increases stability during use.

The pliers feature a non-slip plastic coating and integrated crush protection for improved ergonomics and safety.

Variable, smooth-running quick adjustment thanks to a locking hole.

The inductively hardened jaw teeth provide the water pump pliers with tremendous wear resistance.

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Particularly durable and resistant.

Made from high-quality Chrome Alloy Steel, forged and oil-hardened, the water pump pliers meet the highest standards of robustness and durability. The inductively hardened jaw serration gives the tool additional hardness and wear resistance.



PRODUCT IMAGE
IN PROGRESS

Every action perfectly executed.

The ergonomically designed handles are coated with a non-slip plastic with a rough surface texture. This makes the pliers comfortable to hold and enables fatigue-free working - even with dirty hands. The integrated clamp protection reliably protects against crush injuries.



PRODUCT IMAGE
IN PROGRESS

High stability.

The sliding slip joint with double support ensures exceptional stability and a particularly long service life, even under high loads. The robust design guarantees reliable performance, even under demanding conditions.

Technical attributes.

DIN	DIN ISO 8976
Handles	black lacquered, box frame polished, plastic-coated with sure-grip surface
Header	black lacquered, jaws polished
Length mm (L)	240 mm
Alloy	Chrome Vanadium Steel
Jaw opening max. (mm)	34 mm
Opening width adjustment	7x

Logistics data.

Depth mm (IFS)	224
Width mm (IFS)	15
Height mm (IFS)	50
WEEE/ElektroG	nicht ear-pflichtig
Length (packaged, mm)	224
Width (packaged, mm)	15
Height (packaging, mm)	50
Volume (packaged, dm3)	0.168 dm3
Product no.	65516240
Weight (gross, kg)	0,315
Weight PAP (kg)	0,000
Weight PVC (kg)	0,006
GTIN	4018754037971
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen

Customs tariff no.	82032000
Packing standard	1
Weight (g)	320 g

Variants.

Product no.	Model No. (ERP)	Description	GTIN
65516175	6551 6 175	Water pump pliers L.175mm	4018754206353
65516240	6551 6 240	Water pump pliers L.240mm	4018754037971
65516300	6551 6 300	Water pump pliers L.300mm	4018754170135

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal