



### Water pump pliers FastGRIP

#### 6572

Product no. 65726240

GTIN 4018754178421

Model FastGRIP 6572 240

Label.

Water pump pliers FastGRIP L.240mm

Properties.

- · self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- · quick adjustment of the pliers at the push of a button
- · variable and smooth fine adjustment
- · induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- Chrome Alloy Steel, forged and oil-hardened
- plastic coated handles
- DIN ISO 8976

### Benefits.

Infinitely variable and smooth-running quick adjustment at the push of a button on the tool.

The fine-toothed jaw reliably grips objects of various shapes and holds nuts and pipes securely.

The pliers feature a non-slip plastic coating and built-in crush protection for improved ergonomics and safety.

Sliding slip joint with double support increases stability during use.

The inductively hardened jaw teeth provide the water pump pliers with tremendous wear resistance.

## Product highlights.



#### Flexible quick adjustment.

Adaptation to the workpiece is achieved by precise, multi-stage quick adjustment of the pivot pin. Adjustment takes place quickly and easily via a push button, which makes the use of these pump pliers flexible.



#### Every action perfectly executed.

The ergonomically designed handles are coated with a non-slip plastic with a rough surface texture. This makes the pliers comfortable to hold and enables fatigue-free working - even with dirty hands. The integrated clamp protection reliably protects against crush injuries.



#### Particularly durable and resistant.

Made from high-quality Chrome Alloy Steel, forged and oil-hardened, the water pump pliers meet the highest standards of robustness and durability. The inductively hardened jaw serration gives the tool additional hardness and wear resistance.



#### High stability.

The sliding slip joint with double support ensures exceptional stability and a particularly long service life, even under high loads. The robust design guarantees reliable performance, even under demanding conditions.

## Technical attributes.

## Logistics data.

DIN	DIN ISO 8976	Depth mm (IFS)	250
Handles	plastic overlay with a textured surface	Width mm (IFS)	50
		Height mm (IFS)	20
Header	polished	WEEE/ElektroG	nicht ear-pflichtig
Length mm (L)	240 mm	Length (packaged, mm)	250
Alloy	Chrome Vanadium Steel	Width (packaged, mm)	50
Jaw opening max. (mm)	37 mm	Height (packaging, mm)	20
Opening width adjustment 12x		Volume (packaged, dm3)	0.25 dm3

Product no.	65726240
Weight (gross, kg)	0,395
Weight PAP (kg)	0,000
Weight PVC (kg)	0,006
GTIN	4018754178421
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Customs tariff no.	82032000
Packing standard	1
Weight (g)	405 g

# Variants.

Product no.	Model No. (ERP)	Description	GTIN
65726180	FastGRIP 6572 180	Water pump pliers FastGRIP L.180mm	4018754206377
65726240	FastGRIP 6572 240	Water pump pliers FastGRIP L.240mm	4018754178421
65726300	FastGRIP 6572 300	Water pump pliers FastGRIP L.300mm	4018754206384

# GTIN.

