

Standard MANOSKOP® torque wrenches w.permanently installed ratchet

721 Quick

Product no. 50204030

GTIN 4018754268948 Model 721/30 QUICK







Label.

MANOSKOP® torque wrench 721 Quick 60-300N·m 1/2" L. 553mm

Properties.

- clicking type with dual stop signal
- no reset to "0" required
- the measuring element is only under load when a force is applied.
- Quick adjustment thanks to easy-to-operate locking lever in handle
- non-slip adjuster with thumb recess for quick torque adjustment
- dual scale N·m/ft·lb
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measurement range of the torque wrench)
- optimal calibration with perfectControl® calibration systems
 No. 7794 or calibration systems No. 7706, 7791
- · easy adjustment without disassembly via 2 external adjustment screws
- for controlled clockwise tightening
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- accuracy ± 4%

Benefits.

Made in Germany - STAHLWILLE setting torque wrench, length 553 mm, with calibration certificate (DIN EN ISO 6789-2:2017), 50204030.

Patented, low-wear release system with flexible rod.

Lightning-fast and precise torque adjustment.

Continued loading after release or loading in the opposite direction will not damage the torque wrench.

Product highlights.



Rapid adjustment.

Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.

Technologies and features.



Low-wear bending beam system

Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that the spring does not need to be reset to '0' after use.



2-component handle


Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



DIN EN ISO 6789-2

Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.

Technical drawing.



Technical attributes.

| Scale division N·m | 10 N·m |
|------------------------------|------------------------|
| Scale division ft-lb | 10 ft·lb |
| Measuring range N·m | 60-300 N·m |
| Measuring range ft-lb | 50-220 ft·lb |
| External square drive (inch) | 1/2 |
| Number of teeth | 36 |
| b1 | 28 mm |
| b2 | 44 mm |
| DIN | DIN EN ISO 6789-2:2017 |
| Size | 30 |
| Height mm (h1) | 23 mm |
| Height mm (h2) | 27,5 mm |
| Length mm (L) | 553 mm |
| LF | 486 mm |
| MA N·m | 60 N·m |
| Nominal value N·m | 300 N·m |

Logistics data.

| Depth mm (IFS) | 555 |
|------------------------|---------------------|
| Width mm (IFS) | 46 |
| Height mm (IFS) | 30 |
| WEEE/ElektroG | nicht ear-pflichtig |
| Length (packaged, mm) | 580 |
| Width (packaged, mm) | 46 |
| Height (packaging, mm) | 45 |
| Volume (packaged, dm3) | 1.2006 dm3 |
| Product no. | 50204030 |
| Weight (gross, kg) | 1,810 |
| Weight PAP (kg) | 0,000 |
| Weight PVC (kg) | 0,114 |
| GTIN | 4018754268948 |
| Country of origin AWR | GERMANY |
| Region of origin | Nordrhein-Westfalen |
| Customs tariff no. | 82041100 |
| Packing standard | 1 |
| Weight (g) | 1646 g |

Variants.

| Product no. | Model No. (ERP) | Description | GTIN |
|-------------|-----------------|--|---------------|
| 50204005 | 721/5 QUICK | MANOSKOP® torque wrench 721 Quick 6-50N·m 3/8" L. 352mm | 4018754268917 |
| 50204015 | 721/15 QUICK | MANOSKOP® torque wrench 721 Quick 30-150N·m 1/2" L. 452mm | 4018754268924 |
| 50204020 | 721/20 QUICK | MANOSKOP® torque wrench 721 Quick 40-200N·m 1/2" L. 483mm | 4018754268931 |
| 50204030 | 721/30 QUICK | MANOSKOP® torque wrench 721 Quick 60-300N·m 1/2" L. 553mm | 4018754268948 |

GTIN.



Accessories (for).



81370003 Plastic case, empty

Spare part(s), spare part(s) for.



59191030 Ratchet spare parts sets for torque wrenches No.721

Images.





STAHLWILLE Eduard Wille GmbH