



Torque wrench

730 Quick



Product no. **50184004**
GTIN **4018754292660**
Model **730/4 QUICK**



Label.

Torque wrench service MANOSKOP® (N·m) 730 Quick 8-40N·m 9 x 12 mm L. 223mm

Properties.

- click-type
- the measuring element is only under load while force is being applied, no need for manual reset to zero
- mount for interchangeable insert/shell tools
- QuickRelease safety lock (sizes 5–65)
- rapid setting thanks to easy-action locking lever in the handle (sizes 5–65)
- ergonomically designed, non-slip adjuster with a thumb recess
- magnifying glass integrated in the display window
- optimised convex handle for strain-free working
- dual stop signal
- twin scales N·m/ft·lb and N·m/in·lb (sizes 5–80)
- on request also available as an N·m-only version without twin scale (sizes 5–65)
- can be applied for either clockwise or anticlockwise tightening by turning the inserts over
- any force applied to the tool after the 'click' or applied in the opposite direction to the current function – e.g. forcible loosening of a jammed screw – does not act on the trigger mechanism and cannot cause damage to it
- calibration using perfectControl® calibrating unit No 7794 or calibration system No 7706. Readjustment does not require disassembly.
- certificate in accordance with DIN EN ISO 6789-2:2017
- **display deviation value $\pm 4\%$**



Product highlights.



Rapid adjustment.

Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.


Technologies and features.



QuickRelease

The QuickRelease safety lock prevents unintentional loss of insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change.

Technical drawing.



Technical attributes.

Scale division N·m	1 N·m
Measuring range N·m	8-40 N·m
Width mm (b)	27,5 mm
Size	4
Size square socket [internal square drive]	9 x 12 mm
Height mm (h)	23,6 mm
Length mm (L)	223 mm

Logistics data.

Depth mm (IFS)	225
Width mm (IFS)	43
Height mm (IFS)	30
WEEE/ElektroG	nicht ear-pflichtig
Length (packed, mm)	255
Width (packed, mm)	55
Height (packed, mm)	55

LF	200,8 mm	Volume (packed, dm3)	0.771375 dm3
SF	17,5 mm	Art. no.	50184004
		Weight (gross, kg)	0,478
		Weight PAP (kg)	0,000
		Weight PVC (kg)	0,066
		GTIN	4018754292660
		Country of origin AWR	GERMANY
		Region of origin	Nordrhein-Westfalen
		Customs tariff no.	82041100
		Packing standard	1
		Weight	395 g

Variants.

Art. no.	Model no. (ERP)	Description	GTIN
91381054	730/2-1 BW QUICK	Torque wrench 730 Quick 2-10N·m 9 x 12 mm L. 179mm	4018754320325
50184001	730/2-1 QUICK	Torque wrench service MANOSKOP® (N·m) 730 Quick 2-10N·m 9 x 12 mm L. 179mm	4018754359035
50184002	730/2 QUICK	Torque wrench service MANOSKOP® (N·m) 730 Quick 4-20N·m 9 x 12 mm L. 179mm	4018754292653
50184004	730/4 QUICK	Torque wrench service MANOSKOP® (N·m) 730 Quick 8-40N·m 9 x 12 mm L. 223mm	4018754292660

GTIN.



Accessories (for).



58250004
Fine-tooth ratchet
insert adaptor



58253004
QR ratchet insert tool

Spare part(s) for.



92057436
2-component handle