



## Angle and torque wrench MANOSKOP®

714R



Product no. **96501100**  
GTIN **4018754212804**  
Model **714R/100**



### Label.

Angle and torque wrench MANOSKOP® 714R 100-1000N·m 3/4" L. 1438mm

### Properties.

- with reversible ratchet (size 1-4), fine-tooth reversible ratchet (size 6-65) or insert ratchet insert adaptor with push-through square drive (size 80-100)
- 4 measuring modes (torque, angle of rotation, torque with "angle of rotation" monitoring variable, angle of rotation with "torque" monitoring variable)
- high-resolution colour OLED display and side signal lights
- visual evaluation of the bolted joint: Yellow light (pre-warning threshold reached), green light (within target range), red light (measurement outside tolerance range)
- freely configurable menu structure
- battery compartment cap with bayonet connection
- optional: Li-ion battery no. 7195-2 and charger No. 7160
- 3 function modes: click (patented electromechanical triggering), peak hold (displaying mode with peak value display) and track (displaying mode with actual value display)
- micro USB interface for data communication
- optional Bluetooth low energy-module (5.2)
- QuickRelease security lock - insert tool changing system
- data storage for up to 2,500 tightenings, including date and time stamp
- up to 200 screw joints in a maximum of 25 sequences can be programmed
- different tolerance limits adjustable depending on the type of bolted joint
- acoustic and visual evaluation of the bolted joint
- fast and precise setting via the keypad
- no unintentional adjustments thanks to password-protected keypad lock
- acoustic and visual signal warns of torque wrench overload and forced triggering in clockwise tightening mode
- automatic indication of the next calibration date, user-configurable according to elapsed time and/or number of operations
- fully automatic calibration and adjustment with the perfectControl® calibration and adjustment device No. 7794-2 (torque) or 7794-3 (torque and angle of rotation) for reducing error influencing factors
- units of measurement: N·m, ft·lb, in·lb
- automatic extension length compensation: Possibility of entering a custom extension length to ensure that the required target value is achieved correctly with compensation for the lever extension

- ready for operation again immediately after release
- for controlled clockwise and anticlockwise tightening (sizes 1-65); for anticlockwise tightening in "triggering" function mode the insert tool must be rotated (sizes 80-100)
- visual, acoustic and tactile trigger signal
- torque and angle of rotation simultaneously visible
- measurement regardless of the force application point (for sizes 1, 2 and 4)
- safe handling due to the ergonomically formed 2-component handle (resistant to the most common oils, greases, fuels, brake fluids and Skydrol)
- 3 certificates included (torque displaying/triggering in accordance with DIN EN ISO 6789-2:2017, angle of rotation based on VDI/VDE 2648-2)
- in sturdy plastic box (sizes 40-100 in sheet steel box)
- registered design, patented
- supplied with SensoMaster 4 software, USB cable, 4 micro-batteries AAA/LR03, 1.5 V
- **angle of rotation display resolution 0.1°**
- **angle of rotation display deviation  $\pm 1^\circ$ ,  $\pm 1$  digit to 100°, >100° at least 1%,  $\pm 1$  digit**
- **torque display resolution  $\leq 60$  N·m: 0.01 N·m; > 60 N·m: 0.1 N·m**
- **torque display deviation  $\pm 2\%$ ,  $\pm 1$  digit**

## Benefits.

An angle and torque wrench for bolted joints in accordance with the torque, angle of rotation, torque with "angle of rotation" monitoring variable and angle of rotation with "torque" monitoring variable tightening method.

Visual evaluation of the bolted joint.

Thanks to the combination of the patented electromechanical triggering and the display and acoustic feedback, the wrench provides signalling with maximum optimisation.

Electromechanically displaying (with electronic measurement) and triggering (with the familiar mechanical "click").

Simple documentation of the recorded measurements on the PC via the USB interface and via an optional Bluetooth Low Energy module.

## Product highlights.



### Angle of rotation and torque measurement

Our torque and angle wrenches make it possible to tighten bolted joints in accordance with the torque, angle of rotation, torque with "angle of rotation" monitoring variable and angle of rotation with "torque" monitoring variable tightening method. Thanks to this functional diversity, the wrench is suitable for the most popular tightening methods.




### Electromechanical triggering.

The patented electromechanical MANOSKOP® 714 measures the applied torque electronically. A visual evaluation of the bolted joint is shown by means of a display and side signal lights. Unlike a purely electronic torque wrench, the triggering and haptic user feedback are provided mechanically. A distinctly perceptible jolt and a clearly audible click indicate that the target value has been reached.



### Comprehensive documentation.

Our electromechanical torque wrenches can be documented. They can be easily configured and programmed using the SensoMaster software. This means that all data can be read out, stored and subjected to further processing on the PC for better monitoring and optimisation of the work processes. The digital measurement also allows the actual torque which has been applied (actual value) to be specified after triggering, as well as the target value.



### Also suitable for difficult application areas.

STAHLWILLE electromechanical torque wrenches are ideal for application areas in which electronic torque wrenches are pushed to their signalling limits - such as when working overhead or if the display cannot be read off. Even in noisy, busy and very bright environments which can make it difficult to perceive vibrations or visual and acoustic signals, electromechanical torque wrenches use patented haptic feedback to indicate that the target value has been reached.



### More reliability.

Our electromechanical torque wrenches minimise operating errors. Screw joints and sequence plans, for example, can be parameterised and saved. The torque wrench then automatically sets the triggering torque for the selected bolted joint. The triggering torque is also specified digitally so that parallax effects (errors caused by to an incorrect reading angle), which are possible when using a mechanical scale are eliminated.



### Exchangeable insert tools.

Our MANOSKOP® 714R includes a ratchet insert adaptor. Depending on the size of the torque wrench, this is a reversible ratchet, adjustable fine tooth ratchet or ratchet insert adaptor with push-through square drive. This is not permanently installed, and can be replaced with other insert tools to suit your individual application.

## Technologies and features.



### QuickRelease

The QuickRelease safety lock prevents unintentional loss of insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change.



### 2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



### Factory calibration certificate (ISO calibration)

Our torque tools, transducers, and test equipment are delivered with a factory calibration certificate in accordance with DIN EN ISO 6789-2:2017, and based on DKD-R 10-8 for traceability of the measuring equipment.

## Technical attributes.

Measuring range N·m

100-1000 N·m

## Logistics data.

Depth mm (IFS)

1530

|  |                        |                       |                     |
|--|------------------------|-----------------------|---------------------|
| Measuring range ft·lb                      | 73-735 ft·lb           | Width mm (IFS)        | 130                 |
| Measuring range in·lb                      | 885-8850 in·lb         | Height mm (IFS)       | 100                 |
| External square drive (inch)               | 3/4                    | WEEE/ElektroG         | Großgeräte B2C      |
| Number of teeth                            | 30                     | Length (packed, mm)   | 1530                |
| Battery type                               | Micro (AAA) 1,5V       | Width (packed, mm)    | 130                 |
| Width mm (b)                               | 130 mm                 | Height (packed, mm)   | 100                 |
| DIN  | DIN EN ISO 6789-2:2017 | Volume (packed, dm3)  | 19.89 dm3           |
| Weight with box                            | 12500 g                | Art. no.              | 96501100            |
| Size                                       | 100                    | Weight (gross, kg)    | 12,500              |
| Size square socket [internal square drive] | 22 x 28 mm             | Weight PAP (kg)       | 0,650               |
| Height mm (h)                              | 100 mm                 | Weight PVC (kg)       | 0,000               |
| Length mm (L)                              | 1438 mm                | GTIN                  | 4018754212804       |
|  |                        | Country of origin AWR | GERMANY             |
|  |                        | Region of origin      | Nordrhein-Westfalen |
|  |                        | Customs tariff no.    | 82041100            |
|  |                        | Packing standard      | 1                   |
|  |                        | Weight                | 6905 g              |


## Variants.

| Art. no. | Model no. (ERP) | Description  | GTIN          |
|----------|-----------------|--|---------------|
| 96501001 | 714R/ 1         | Angle and torque wrench MANOSKOP®<br>714R 1-10N·m 1/4" L. 269mm      | 4018754212712 |
| 96501002 | 714R/ 2         | Angle and torque wrench MANOSKOP®<br>714R 2-20N·m 1/4" L. 269mm      | 4018754212729 |
| 96501004 | 714R/ 4         | Angle and torque wrench MANOSKOP®<br>714R 4-40N·m 1/4" L. 295mm      | 4018754212736 |
| 96501006 | 714R/ 6         | Angle and torque wrench MANOSKOP®<br>714R 6-60N·m 3/8" L. 427mm      | 4018754212743 |
| 96501010 | 714R/10         | Angle and torque wrench MANOSKOP®<br>714R 10-100N·m 1/2" L. 500mm    | 4018754212750 |
| 96501020 | 714R/20         | Angle and torque wrench MANOSKOP®<br>714R 20-200N·m 1/2" L. 594mm    | 4018754212767 |
| 96501040 | 714R/40         | Angle and torque wrench MANOSKOP®<br>714R 40-400N·m 3/4" L. 737mm    | 4018754212774 |
| 96501065 | 714R/65         | Angle and torque wrench MANOSKOP®<br>714R 65-650N·m 3/4" L. 980mm    | 4018754212781 |
| 96501080 | 714R/80         | Angle and torque wrench MANOSKOP®<br>714R 80-800N·m 3/4" L. 1253mm   | 4018754212798 |
| 96501100 | 714R/100        | Angle and torque wrench MANOSKOP®<br>714R 100-1000N·m 3/4" L. 1438mm | 4018754212804 |

GTIN.



## Accessories (for).



96585235  
SENSOMASTER Live  
software



96521161  
Interface adaptor set



52110162  
Rest for docking station  
No.7762



52110062  
Docking station for  
No.714



52110061  
Interface adaptor



54101195  
Li-ion battery for  
No.714



52110220  
Bluetooth Low Energy  
module 714