



SERVICE-MANOSKOP® torque wrench 730R Quick



Product no. **96504005**
GTIN **4018754269488**
Model **730R/5 QUICK**



Label.

SERVICE-MANOSKOP torque wrench 730R Quick 6-50N·m 3/8" L. 380mm

Properties.

- releasing
- No reset to "0" necessary, as measuring element is only loaded during the tightening process
- receptacle for interchangeable plug-in tools
- QuickRelease safety lock
- Flash adjustment by easy-to-operate clamping lever in the handle
- ergonomically shaped, non-slip adjustment element with thumb recess
- optimised ball handle for fatigue-free working
- double stop signal
- double scale N·m/ft·lb or N·m/in·lb
- on request also available as N·m version only without double scale
- left-hand tightening by turning over the plug-in tools
- further loads after releasing or loads against the functional direction, e.g. with stuck screws, do not affect the releasing mechanism, which is thus protected against damage
- calibration with the perfectControl® calibration device no. 7794 or the calibration system no. 7706. If necessary, readjustment without disassembly
- certificate according to DIN EN ISO 6789-2:2017
- display deviation $\pm 4\%$

Product highlights.



Rapid adjustment.


Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.



Adjustment does not require disassembly.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.


Technologies and features.



Low-wear flexible rod system

Our torque wrench is equipped with a low-wear trigger system with a bending beam. Unlike conventional torque wrenches with coiled springs, the flexible rod is not preloaded in unloaded state, which means that the 'spring' does not need to be reset to '0' after use.

Technical drawing.



Technical attributes.

Scale division N·m	2 N·m
Measuring range N·m	6-50 N·m
Measuring range ft·lb	5-36 ft·lb
External square drive (inch)	3/8
b1	50 mm
b2	33 mm
DIN	DIN EN ISO 6789-2:2017
Size	5
Size square socket [internal square drive]	9 x 12 mm
Height mm (h)	50 mm
Length mm (L)	380 mm
LF	288 mm
SF	17,5 mm

Logistics data.

Depth mm (IFS)	380
Width mm (IFS)	50
Height mm (IFS)	50
WEEE/ElektroG	nicht ear-pflichtig
Length (packed, mm)	380
Width (packed, mm)	50
Height (packed, mm)	50
Volume (packed, dm ³)	0.95 dm ³
Art. no.	96504005
Weight (gross, kg)	0,994
Weight PAP (kg)	0,000
Weight PVC (kg)	0,068
GTIN	4018754269488
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Customs tariff no.	82041100
Packing standard	1

Weight

994 g

Variants.

Art. no.	Model no. (ERP)	Description	GTIN
96501054	730R/2-1 Quick	Torque wrench MANOSKOP® 730R Quick 2-10N·m 1/4" L. 250mm	4018754339976
96504002	730R/2 QUICK	SERVICE-MANOSKOP torque wrench 730R Quick 4-20N·m 3/8" L. 255mm	4018754311354
96504004	730R/4 QUICK	Torque wrench MANOSKOP® 730R Quick 8-40N·m 3/8" L. 285mm	4018754311361
96504005	730R/5 QUICK	SERVICE-MANOSKOP torque wrench 730R Quick 6-50N·m 3/8" L. 380mm	4018754269488
96504010	730R/10 QUICK	Torque wrench MANOSKOP® 730R Quick 20-100N·m 1/2" L. 430mm	4018754269495
96504012	730R/12 QUICK	SERVICE-MANOSKOP torque wrench 730R Quick 25-130N·m 1/2" L. 475mm	4018754269501
96504020	730R/20 QUICK	SERVICE-MANOSKOP torque wrench 730R Quick 40-200N·m 1/2" L. 530mm	4018754269518
96504030	730R/30 QUICK	Torque wrench MANOSKOP® 730R Quick 60-300N·m 1/2" L. 590mm	4018754326006
96504040	730R/40 QUICK	Torque wrench MANOSKOP® 730R Quick 80-400N·m 3/4" L. 675mm	4018754269525
96504565	730RII/65 QUICK	Torque wrench MANOSKOP® 730R Quick 130-650N·m 3/4" L. 1125mm	4018754269563

GTIN.



Images.



