



Torque screwdriver sets

TORSIOTRONIC® 10/29

Product no. **96510000**
GTIN **4018754323289**
Model **TORSIOTRONIC 10/29**



Label.

Torque screwdriver set Model TORSIOTRONIC® 10/29 29 pcs.

Properties.

Key features of torque screwdriver TORSIOTRONIC®

- electromechanically indicating and clicking
- for clockwise and counter-clockwise tightening
- visual, acoustic, and haptic stop signal
- with 1/4" external square drive (6.3 DIN 3120/ISO 1174-1) and integrated ratchet function with 80 teeth, ratchet angle of 4.5°, for 1/4" sockets
- after clicking, the clutch mechanism prevents unintended overshooting of the set tightening torque and overtightening of the screw is not possible
- bright and energy-efficient OLED colour display - readable from virtually any angle
- optical evaluation of the applied torque by traffic light colours on the display and LEDs at the side
- supported languages: DE, EN, IT, FR, ES
- stores up to 2,500 joint and sequence results, for transfer to the PC via an integrated micro-USB interface
- tolerances for evaluation purposes can be set individually
- short training time thanks to intuitive controls and an easy-to-understand menu structure
- three operating modes (Click, Track, Peak-Hold)
- bolted joints and sequences can be programmed
- with a 1/4" inner square at the end of the handle (6.3 DIN 3120/ISO 1174-1) for accommodating a 1/4" T-handle
- units of measurement: cN·m, N·m, ft·lb, in·lb, in·oz
- the GEN3 version can charge the installed battery via the micro USB cable
- long battery life with battery-saving standby mode
- the batteries are quick and easy to change.
- supplied with 3.6 V lithium battery, type 18650, packaged according to UN 3481
- with 2-component handle
- patented
- in a sturdy plastic box
- calibration certificate in accordance with DIN EN ISO 6789-2:2017

• **accuracy ± 4%**

Contains 29-pieces:

1 electromechanical torque screwdriver 1/4" **No. TORSIOTRONIC® 10**: measurement range: 100-1000 cN·m
 8 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10 mm
 3 bits PHILLIPS® 1/4" **No. PH 1221-1223**: PH1; PH2, PH3
 3 bits POZIDRIV® 1/4" **No. PZ 1221-1223**: PZ1; PZ2, PZ3
 4 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6 mm
 5 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20
 5 screwdriver sockets TORX® with hole 1/4" **No. 44 KTXB**: T8; T9; T10; T15; T20
 + sturdy plastic box, SensoMaster 4 software, USB cable, bit holder, T-handle (size 10), insulating washer, lithium battery 3.6 V, type 18650, packed in accordance with UN 3481

Technologies and features.



Factory calibration certificate (ISO calibration)

Our torque tools, transducers, and test equipment are delivered with a factory calibration certificate in accordance with DIN EN ISO 6789-2:2017, and based on DKD-R 10-8 for traceability of the measuring equipment.



2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.

Technical attributes.

Measuring range N·m	1-10 N·m
Measuring range cN·m	100-1000 cN·m
Measuring range ft·lb	0,7-7,3 ft·lb
Measuring range in·lb	8,8-88,5 in·lb
Measuring range in·oz	141-1417 in·oz
Number of tools	29 pcs.
Battery type	Lithium 3.6 V type 18650
Width mm (b)	227 mm
DIN	DIN 3120 / ISO 1174-1
Height mm (h)	70 mm
Length mm (L)	420 mm

Logistics data.

Depth mm (IFS)	420
Width mm (IFS)	227
Height mm (IFS)	70
WEEE/ElektroG	Kleingeräte B2C
Length (packaged, mm)	420
Width (packaged, mm)	227
Height (packaging, mm)	70
Volume (packaged, dm ³)	6.6738 dm ³
Product no.	96510000
Weight (gross, kg)	2,000
Weight PAP (kg)	0,000
Weight PVC (kg)	0,000
GTIN	4018754323289

Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Customs tariff no.	82041100
Packing standard	1
Weight (g)	2000 g

Variants.

Product no.	Model No. (ERP)	Description	GTIN
96510000	TORSIOTRONIC 10/29	Torque screwdriver set Model TORSIOTRONIC® 10/29 29 pcs.	4018754323289

GTIN.



STAHLWILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-393

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal