



## Precision feeler gauges

11095-11097

Product no. **74240001**  
GTIN **4018754045549**  
Model **11095/13**

**Label.** Precision feeler gauges No.11095/13

**Properties.**

- tapered blades made of hardened spring steel
- nickel-plated case with locking screw
- tolerance according to T2

## Benefits.

In nickel-plated shell with conical sheets, length 100 mm.

Thickness 0.05 - 1.0 mm, graduated in 0.05 mm increments.

## Technical attributes.

|                   |                                                                                                         |
|-------------------|---------------------------------------------------------------------------------------------------------|
| Sheet thickness " | 0,002; 0,004; 0,006;<br>0,008; 0,010; 0,012;<br>0,016; 0,020; 0,024;<br>0,028; 0,032; 0,036;<br>0,040 " |
| Sheet thickness   | 0,05; 0,10; 0,15; 0,20;<br>0,25; 0,30; 0,40; 0,50;<br>0,60; 0,70; 0,80; 0,90;<br>1,00 mm                |
| Number of sheets  | 13                                                                                                      |
| Length mm (L)     | 100 mm                                                                                                  |
| Model No.         | 11095/13                                                                                                |

## Logistics data.

|                        |                     |
|------------------------|---------------------|
| Depth mm (IFS)         | 103                 |
| Width mm (IFS)         | 15                  |
| Height mm (IFS)        | 13                  |
| WEEE/ElektroG          | nicht ear-pflichtig |
| Length (packaged, mm)  | 120                 |
| Width (packaged, mm)   | 62                  |
| Height (packaging, mm) | 35                  |
| Volume (packaged, dm3) | 0.2604 dm3          |
| Product no.            | 74240001            |
| Weight (gross, kg)     | 0,620               |
| Weight PAP (kg)        | 0,022               |
| Weight PVC (kg)        | 0,000               |
| GTIN                   | 4018754045549       |

|                       |                        |
|-----------------------|------------------------|
| Country of origin AWR | CHINA                  |
| Region of origin      | Ausländischer Ursprung |
| Customs tariff no.    | 90318020               |
| Packing standard      | 10                     |
| Weight (g)            | 62 g                   |

Variants.

| Product no. | Model No. (ERP) | Description                         | GTIN          |
|-------------|-----------------|-------------------------------------|---------------|
| 74240001    | 11095/13        | Precision feeler gauges No.11095/13 | 4018754045549 |
| 74240002    | 11095/20        | Precision feeler gauge No.11095/20  | 4018754045556 |
| 74240005    | 11097/26        | Precision feeler gauge No.11097/26  | 4018754187607 |

GTIN.



Images.

Zulässige Toleranzen für Federbandstahl, gehärtet

| Nennbreite mm             | T2 (A2) +/- mm | T3 (A3) +/- mm |
|---------------------------|----------------|----------------|
| 0,03 / 0,04 / 0,05 / 0,06 | 0,004          | 0,003          |
| 0,07 / 0,08 / 0,09 / 0,10 | 0,005          | 0,004          |
| 0,11 / 0,12 / 0,13        | 0,005          | -              |
| 0,14 / 0,15               | 0,006          | 0,005          |
| 0,16 / 0,18               | 0,007          | -              |
| 0,20                      | 0,008          | 0,006          |
| 0,22 / 0,24               | 0,008          | -              |
| 0,25                      | 0,009          | 0,006          |
| 0,28                      | 0,009          | -              |
| 0,30                      | 0,009          | 0,007          |
| 0,35                      | 0,011          | 0,007          |
| 0,40 / 0,45               | 0,012          | 0,008          |
| 0,50 / 0,55               | 0,014          | 0,009          |
| 0,60 / 0,65               | 0,014          | 0,009          |
| 0,70 / 0,75               | 0,017          | 0,012          |
| 0,80 / 0,85               | 0,019          | 0,013          |
| 0,90 / 0,95               | 0,022          | 0,014          |
| 1,00                      | 0,024          | 0,016          |
| 1,10                      | 0,024          | 0,017          |
| 1,20                      | 0,024          | 0,018          |
| 1,30                      | 0,028          | 0,019          |
| 1,40                      | 0,028          | 0,021          |
| 1,50                      | 0,028          | 0,022          |
| 1,60                      | 0,033          | 0,023          |
| 1,70                      | 0,033          | 0,024          |
| 1,80                      | 0,033          | 0,026          |
| 1,90                      | 0,035          | 0,027          |
| 2,00                      | 0,035          | 0,028          |