



Combination spanner set OPEN BOX, metric

OPEN BOX 14



Product no. **96401007**
GTIN **4018754095964**
Model **OPEN BOX 14/10**



Label.

Combination spanner set OPEN BOX 14/10 8-19 10 pcs.

Properties.

- **metric, identical** end sizes
- long design for higher power transmission
- ring-end cranked 10°, jaw angled 15°
- reinforcement between jaw and shaft
- durable, slim and lightweight design
- extremely resilient and durable
- high flexural strength due to double-T profile
- STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
- drop-forged, hardened, and cooled in an oil bath
- Chrome Alloy Steel, chrome-plated
- DIN 3113 Form B/ISO 7738 Form B
- in sturdy cardboard packaging

Benefits.

High-quality 10 pcs.-piece combination spanner set in metric sizes.

Special manufacturing process makes thin-walled rings possible - perfect for working in places that are difficult to access.

The long force loading point requires less effort with constant torque.

The AS-Drive profile prevents damage to the fastener caused by force being applied to the edges of the nut or bolt.



Product highlights.



PRODUCT IMAGE
IN PROGRESS

Non-slip surface

STAHLWILLE spanners have a high-quality surface finish with good grip, making it possible to work safely and efficiently, even with greasy hands. The non-slip property improves control during handling.



A solution for every situation.

Our combination spanners are available in different versions (metric, imperial, long, with Spline-Drive profile) and as sets in textile bags, roll-up tool pouches or TCS inlays.

Technologies and features.



Anti-Slip-Drive

The special AS-Drive profile makes high force transmission to the flats of screws and bolts possible without damaging them. This also prevents stripping of the screw head.



Double-T profile

Our combination and ring spanners have an additional recess in the middle of the tool. Similar to the principle of a double-T beam, this provides a tremendous load capacity and maximum strength whilst reducing weight.



Thin-walled rings

The thin wall diameter of our rings makes it easier to work in confined spaces. The ring sides are taller than standard nuts, which prevents jamming.



Offset Shaft Design

Our spanners are specially designed with additional reinforcement in the load zones where the greatest amount of force is transmitted - namely where the jaw meets the shank - in order to prevent deformation.

Technical drawing.



Technical attributes.

Number of tools	10 pcs.
Range	8-19
DIN	DIN 3113 Form B / ISO 7738 Form B
Contents	8; 10; 11; 12; 13; 14; 16; 17; 18; 19 mm
Alloy	Chrome Alloy Steel
Jaws angled	10 °
Model No.	14/10 KT
Surface	chrome-plated

Logistics data.

Depth mm (IFS)	410
Width mm (IFS)	182
Height mm (IFS)	35
WEEE/ElektroG	nicht ear-pflichtig
Length (packaged, mm)	410
Width (packaged, mm)	182
Height (packaging, mm)	35
Volume (packaged, dm3)	2.6117 dm3
Product no.	96401007
Weight (gross, kg)	1,235
Weight PAP (kg)	0,000
Weight PVC (kg)	0,010
GTIN	4018754095964
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Packaging	in robust roll-up tool pouch
Customs tariff no.	82041100
Packing standard	1
Weight (g)	1235 g

Variants.

Product no.	Model No. (ERP)	Description	GTIN
96401010	OPEN BOX 14/15N	Combination spanner set OPEN BOX 14/15N 10-30 15 pcs.	4018754122936
96401007	OPEN BOX 14/10	Combination spanner set OPEN BOX 14/10 8-19 10 pcs.	4018754095964

GTIN.



Images.



STAHLWILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-393

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal