



Water pump pliers

6551



Product no. **65516175**
GTIN **4018754206353**
Model **6551 6 175**

Label. Water pump pliers Jaw w.24mm L.175mm

Properties.

- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- Chrome Alloy Steel, forged and oil-hardened
- plastic coated handles
- DIN ISO 8976 (No. 207 C)

Benefits.

Sturdy water pump pliers for gripping, holding, pressing and bending workpieces (thin sheet metal, nuts, screws, etc.).

Sliding slip joint with double support increases stability during use.

The pliers feature a non-slip plastic coating and integrated crush protection for improved ergonomics and safety.

Variable, smooth-running quick adjustment thanks to a locking hole.

The inductively hardened jaw teeth provide the water pump pliers with tremendous wear resistance.

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Every action perfectly executed.

For precise work and powerful gripping - STAHLWILLE pliers with non-slip handle. The comfortable handles with rough surface structure allow safe, low-fatigue work, even with smeared hands.



PRODUCT IMAGE
IN PROGRESS

Particularly durable and resistant.

Made from high-quality Chrome Alloy Steel, forged and oil-hardened, the water pump pliers meet the highest standards of robustness and durability. The inductively hardened jaw serration gives the tool additional hardness and wear resistance.



PRODUCT IMAGE
IN PROGRESS

A secure hold and comfortable handling.

The ergonomically designed handles are coated with a non-slip plastic with a rough surface texture. This makes the pliers comfortable to hold and enables fatigue-free working - even with dirty hands. The integrated clamp protection reliably protects against crush injuries.



PRODUCT IMAGE
IN PROGRESS

High stability.

The sliding slip joint with double support ensures exceptional stability and a particularly long service life, even under high loads. The robust design guarantees reliable performance, even under demanding conditions.

Technical attributes.

DIN	DIN ISO 8976
Handles	black lacquered, box frame polished, plastic-coated with sure-grip surface
Header	black lacquered, jaws polished
Length mm (L)	175 mm
Alloy	Chrome Vanadium Steel

Logistics data.

Depth mm (IFS)	175
Width mm (IFS)	35
Height mm (IFS)	10
WEEE/ElektroG	nicht ear-pflichtig
Length (packaged, mm)	175
Width (packaged, mm)	35
Height (packaging, mm)	10
Volume (packaged, dm3)	0.06125 dm3

Jaw opening max. (mm) 24 mm
Opening width adjustment 6x
Physical length [mm] 177 mm

Product no. 65516175
Weight (gross, kg) 0,173
Weight PAP (kg) 0,000
Weight PVC (kg) 0,005
GTIN 4018754206353
Country of origin AWR GERMANY
Region of origin Nordrhein-Westfalen
Customs tariff no. 82032000
Packing standard 1
Weight (g) 173 g

Variants.

Product no.	Model No. (ERP)	Description	GTIN
65516175	6551 6 175	Water pump pliers Jaw w.24mm L.175mm	4018754206353
65516240	6551 6 240	Water pump pliers Jaw w.34mm L.240mm	4018754037971
65516300	6551 6 300	Water pump pliers Jaw w.45mm L.300mm	4018754170135

GTIN.

