



Precision feeler gauge

11095-11097



Product no. **74240005**
GTIN **4018754187607**
Model **11097/26**

Label. Precision feeler gauge No.11097/26

Properties.

- tapered blades made of hardened spring steel
- nickel-plated case with locking screw
- tolerance according to T2

Benefits.

In nickel-plated shell with conical sheets, length 100 mm.

Thickness 0.05 - 1.0 mm, graduated in 0.05 mm increments.

Technical attributes.

Sheet thickness	0,03; 0,04; 0,05; 0,06; 0,07; 0,08; 0,09; 0,10; 0,15; 0,20; 0,25; 0,30; 0,35; 0,40; 0,45; 0,50; 0,55; 0,60; 0,65; 0,70; 0,75; 0,80; 0,85; 0,90; 0,95; 1,00 mm
Sheet thickness "	0,0012; 0,0016; 0,002; 0,0024; 0,0028; 0,003; 0,0035; 0,004; 0,006; 0,008; 0,010; 0,012; 0,014; 0,016; 0,018; 0,020; 0,022; 0,024; 0,026; 0,028; 0,030; 0,032; 0,034; 0,036; 0,038; 0,040 "
Number of sheets	26
Length mm (L)	100 mm

Logistics data.

Depth mm (IFS)	100
Width mm (IFS)	18
Height mm (IFS)	15
WEEE/ElektroG	nicht ear-pflichtig
Length (packaged, mm)	120
Width (packaged, mm)	67
Height (packaging, mm)	44
Volume (packaged, dm3)	0.35376 dm3
Product no.	74240005
Weight (gross, kg)	0,880
Weight PAP (kg)	0,038
Weight PVC (kg)	0,000
GTIN	4018754187607

Model No.	11097/26	Country of origin AWR	CHINA
		Region of origin	Ausländischer Ursprung
		Customs tariff no.	90318020
		Packing standard	10
		Weight (g)	80 g

Variants.

Product no.	Model No. (ERP)	Description	GTIN
74240001	11095/13	Precision feeler gauges No.11095/13	4018754045549
74240002	11095/20	Precision feeler gauge No.11095/20	4018754045556
74240005	11097/26	Precision feeler gauge No.11097/26	4018754187607

GTIN.



Images.

Zulässige Toleranzen für Federbandstahl, gehärtet

Nennstärke mm Thickness mm	T2 (A2) +/- mm	T3 (A3) +/- mm
0.03 / 0.04 / 0.05 / 0.06	0.004	0.003
0.07 / 0.08 / 0.09 / 0.10	0.005	0.004
0.11 / 0.12 / 0.13	0.005	-
0.14 / 0.15	0.006	0.005
0.16 / 0.18	0.007	-
0.20	0.008	0.006
0.22 / 0.24	0.008	-
0.25	0.009	0.006
0.28	0.009	-
0.30	0.009	0.007
0.35	0.011	0.007
0.40 / 0.45	0.012	0.008
0.50 / 0.55	0.014	0.009
0.60 / 0.65	0.014	0.009
0.70 / 0.75	0.017	0.012
0.80 / 0.85	0.019	0.013
0.90 / 0.95	0.022	0.014
1.00	0.024	0.016
1.10	0.024	0.017
1.20	0.024	0.018
1.30	0.028	0.019
1.40	0.028	0.021
1.50	0.028	0.022
1.60	0.033	0.023
1.70	0.033	0.024
1.80	0.033	0.026
1.90	0.035	0.027
2.00	0.035	0.028