



Combination spanner set

OPEN BOX 14



Product no. **96401004**
GTIN **4018754080700**
Model **OPEN BOX 14/15**



Label.

Combination spanner set OPEN BOX 14/15 6-32 15 pcs.

Properties.

- **metric, identical** end sizes
- long design for higher power transmission
- ring-end cranked 10°, jaw angled 15°
- reinforcement between jaw and shaft
- durable, slim and lightweight design
- extremely resilient and durable
- high flexural strength due to double-T profile
- STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
- drop-forged, hardened, and cooled in an oil bath
- Chrome Alloy Steel, chrome-plated
- DIN 3113 Form B/ISO 7738 Form B
- in robust polyester roll-up tool pouch with Velcro closure
- mesh inserts allow visibility of the tools
- a compact storage solution to keep your tools safe

Benefits.

Made in Germany - Combination spanner set, 15 pcs., 6-32 mm, ring side angled 15°, DIN 3113 Form B / ISO 7738 Form B, Chrome Alloy Steel.

Special manufacturing process makes thin-walled rings possible - perfect for working in places that are difficult to access.

The practical roll-up tool pouch provides a well-organised storage solution.

The long force loading point requires less effort with constant torque.

The AS-Drive profile prevents damage to the fastener caused by force being applied to the edges of the nut or bolt.



Product highlights.



PRODUCT IMAGE
IN PROGRESS

Non-slip surface

STAHLWILLE spanners have a high-quality surface finish with good grip, making it possible to work safely and efficiently, even with greasy hands. The non-slip property improves control during handling.



A solution for every situation.

Our combination spanners are available in different versions (metric, imperial, long, with Spline-Drive profile) and as sets in textile bags, roll-up tool pouches or TCS inlays.



Organised storage.

The set is stored in the pockets of a practical roll-up tool pouch. This makes it convenient and space-saving to carry around. Transparent mesh inserts allow you to see at a glance whether your tools are complete.

Technologies and features.



Double-T profile

Our ring, open-ended and combination spanners have an additional recess in the middle of the tool. Similar to the principle of a double-T beam, this provides a tremendous load capacity and maximum strength whilst reducing weight.



Thin-walled rings

The thin-walled diameter of our rings makes it easier to work in confined spaces. The ring wall is deeper than standard nuts, which prevents jamming.



Offset Shaft Design

Our spanners are specially designed with additional reinforcement in the load zones where the greatest amount of force is transmitted - namely where the jaw meets the shank - in order to prevent deformation.

Technical drawing.



Technical attributes.

Number of tools	15 pcs.
Range	6-32
DIN	DIN 3113 Form B / ISO 7738 Form B
Contents	6; 7; 8; 9; 10; 11; 12; 13; 17; 19; 22; 24; 27; 30; 32 mm
Alloy	Chrome Alloy Steel
Jaws angled	10 °
Surface	chrome-plated
Model No.	14/15

Logistics data.

Depth mm (IFS)	475
Width mm (IFS)	90
Height mm (IFS)	85
WEEE/ElektroG	nicht ear-pflichtig
Length (packaged, mm)	475
Width (packaged, mm)	90
Height (packaging, mm)	85
Volume (packaged, dm3)	3.63375 dm3
Product no.	96401004
Weight (gross, kg)	4,000
Weight PAP (kg)	0,000
Weight PVC (kg)	0,004
GTIN	4018754080700

Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Customs tariff no.	82041100
Packing standard	1
Weight (g)	3370 g

Variants.

Product no.	Model No. (ERP)	Description	GTIN
96401008	OPEN BOX 14/6	Combination spanner set OPEN BOX 14/6 10-24 6 pcs.	4018754122912
96400308	OPEN BOX 14/8 EXTRA	Combination spanner set OPEN BOX 14/8 EXTRA 8-19 8 pcs.	4018754291205
96401009	OPEN BOX 14/9	Combination spanner set OPEN BOX 14/9 10-30 9 pcs.	4018754122929
96401006	OPEN BOX 14/11	Combination spanner set OPEN BOX 14/11 8-22 11 pcs.	4018754080724
96401004	OPEN BOX 14/15	Combination spanner set OPEN BOX 14/15 6-32 15 pcs.	4018754080700
96401005	OPEN BOX 14/17	Combination spanner set OPEN BOX 14/17 6-22 17 pcs.	4018754080717

GTIN.



Images.



