

Penlight

13126-2



Product no. **77490012**
 GTIN **4018754240579**
 Model **12126/2**



Label.

Penlight 40 lm

Properties.

- Ex-rated for zone 1
- powerful, extremely durable LEDs
- sturdy, electrically non-conductive, corrosion-resistant housing made of ABS/polycarbonate
- high impact resistance and reduced glare due to rubberised light head
- consistently bright beam for more than 80% of the life of the alkaline batteries due to eLED electronics
- rubberised front pressure switch for permanent and temporary light
- easy storage with built-in clip holder close to the lamp head
- waterproof to IP67 in water depths up to 1 m
- brightness: 40 lm
- lighting range: 67 m
- lighting duration: 2.5 hours
- batteries: 2 micro-batteries AAA/LR03, alkaline, 1.5 V (not included)
- certifications: II 2G Ex ib IIB T4 Gb, II 2D Ex ib IIIC T60 °C Db, SEV 11 ATEX 0174 X

Technical attributes.

Length mm (L)	132 mm
Width mm (b)	22 mm
Height mm (h)	24 mm
Brightness	40 lm
Protection class	IP67

Logistics data.

Product no.	77490012
GTIN	4018754240579
Weight (g)	55 g
Volume (packaged, dm ³)	0.08694 dm ³
Packing standard	1
WEEE/ElektroG	Kleingeräte B2C
Customs tariff no.	85131000
Country of origin AWR	UNITED STATES
Region of origin	Ausländischer Ursprung
Depth mm (IFS)	135

Width mm (IFS)	28
Height mm (IFS)	23
Weight (gross, kg)	0,042
Weight PAP (kg)	0,000
Weight PVC (kg)	0,000
Length (packaged, mm)	135
Width (packaged, mm)	28
Height (packaging, mm)	23

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal