

## Water pump pliers FastGRIP

**6572**



Product no. **65726240**  
GTIN **4018754178421**  
Model **FastGRIP 6572 240**

**Label.** Water pump pliers FastGRIP L.240mm

### Properties.

- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- quick adjustment of the pliers at the push of a button
- variable and smooth fine adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- Chrome Alloy Steel, forged and oil-hardened
- plastic coated handles
- DIN ISO 8976

### Benefits.

Infinitely variable and smooth-running quick adjustment at the push of a button on the tool.

The fine-toothed jaw reliably grips objects of various shapes and holds nuts and pipes securely.

The pliers feature a non-slip plastic coating and built-in crush protection for improved ergonomics and safety.

Sliding slip joint with double support increases stability during use.

The inductively hardened jaw teeth provide the water pump pliers with tremendous wear resistance.

## Product highlights.



PRODUCT IMAGE  
IN PROGRESS

### Flexible quick adjustment.

Adaptation to the workpiece is achieved by precise, multi-stage quick adjustment of the pivot pin. Adjustment takes place quickly and easily via a push button, which makes the use of these pump pliers flexible.



PRODUCT IMAGE  
IN PROGRESS

### Every action perfectly executed.

The ergonomically designed handles are coated with a non-slip plastic with a rough surface texture. This makes the pliers comfortable to hold and enables fatigue-free working - even with dirty hands. The integrated clamp protection reliably protects against crush injuries.



PRODUCT IMAGE  
IN PROGRESS

### Particularly durable and resistant.

Made from high-quality Chrome Alloy Steel, forged and oil-hardened, the water pump pliers meet the highest standards of robustness and durability. The inductively hardened jaw serration gives the tool additional hardness and wear resistance.



PRODUCT IMAGE  
IN PROGRESS

### High stability.

The sliding slip joint with double support ensures exceptional stability and a particularly long service life, even under high loads. The robust design guarantees reliable performance, even under demanding conditions.

## Technical attributes.

Jaw opening max. (mm)	37 mm
Length mm (L)	240 mm
Header	polished
Handles	plastic overlay with a textured surface
DIN	DIN ISO 8976
Alloy	Chrome Vanadium Steel
Opening width adjustment	12x

## Logistics data.

Product no.	65726240
GTIN	4018754178421
Weight (g)	405 g
Volume (packaged, dm <sup>3</sup> )	0.25 dm <sup>3</sup>
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82032000
Country of origin AWR	GERMANY

<b>Region of origin</b>	Nordrhein-Westfalen
<b>Depth mm (IFS)</b>	250
<b>Width mm (IFS)</b>	50
<b>Height mm (IFS)</b>	20
<b>Weight (gross, kg)</b>	0,395
<b>Weight PAP (kg)</b>	0,000
<b>Weight PVC (kg)</b>	0,006
<b>Length (packaged, mm)</b>	250
<b>Width (packaged, mm)</b>	50
<b>Height (packaging, mm)</b>	20

**GTIN.**



**STAHLWILLE Eduard Wille GmbH**

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal