



IMPACT sockets 3/4"

55IMP

Product no. 25010036
GTIN 4018754015771
Model 55 IMP 36



Label. IMPACT socket 3/4 " 36mm L.57mm

- Properties.**
- with hex
 - 3/4" internal square drive
 - Chrome Alloy Steel, gunmetal finish
 - DIN 3129 / ISO 1711-2

Product highlights.



Optimised functionality.

All IMPACT sockets have a through cross hole for the connecting pin and a deep groove for the rubber locking ring. The locking pin is not stressed during use.


High fitting accuracy.

The high fitting accuracy due to tight tolerances guarantees optimum, backlash-free transmission of forces to the socket.



PRODUCT IMAGE
IN PROGRESS

Technical drawing.



Technical attributes.

| | |
|---------------------------|-----------------------|
| Size [mm] | 36 mm |
| Square drive inner (inch) | 3/4 " |
| Length mm (L) | 57 mm |
| Drive profile | hex |
| d1 | 54,9 mm |
| d2 | 44 mm |
| DIN | DIN 3129 / ISO 1711-2 |
| Alloy | Chrome Alloy Steel |
| t | 32 mm |

Logistics data.

| | |
|------------------------|---------------------|
| Product no. | 25010036 |
| GTIN | 4018754015771 |
| Weight (g) | 545 g |
| Volume (packaged, dm3) | 0.347985 dm3 |
| Packing standard | 2 |
| WEEE/ElektroG | nicht ear-pflichtig |
| Customs tariff no. | 82042000 |
| Country of origin AWR | GERMANY |
| Region of origin | Nordrhein-Westfalen |
| Depth mm (IFS) | 57 |
| Width mm (IFS) | 55 |
| Height mm (IFS) | 55 |
| Weight (gross, kg) | 1,090 |
| Weight PAP (kg) | 0,000 |
| Weight PVC (kg) | 0,007 |
| Length (packaged, mm) | 111 |
| Width (packaged, mm) | 55 |
| Height (packaging, mm) | 57 |

GTIN.



Accessories (for).



39023540
IMPACT locking pin



39013650
IMPACT rubber ring