

Water pump pliers

6551



Product no. **65516175**
GTIN **4018754206353**
Model **6551 6 175**

Label. Water pump pliers L.175mm

Properties.

- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- Chrome Alloy Steel, forged and oil-hardened
- plastic coated handles
- DIN ISO 8976 (No. 207 C)

Benefits.

Sturdy water pump pliers for gripping, holding, pressing and bending workpieces (thin sheet metal, nuts, screws, etc.).

Sliding slip joint with double support increases stability during use.

The pliers feature a non-slip plastic coating and integrated crush protection for improved ergonomics and safety.

Variable, smooth-running quick adjustment thanks to a locking hole.

The inductively hardened jaw teeth provide the water pump pliers with tremendous wear resistance.

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Particularly durable and resistant.

Made from high-quality Chrome Alloy Steel, forged and oil-hardened, the water pump pliers meet the highest standards of robustness and durability. The inductively hardened jaw serration gives the tool additional hardness and wear resistance.



PRODUCT IMAGE
IN PROGRESS

Every action perfectly executed.

The ergonomically designed handles are coated with a non-slip plastic with a rough surface texture. This makes the pliers comfortable to hold and enables fatigue-free working - even with dirty hands. The integrated clamp protection reliably protects against crush injuries.



PRODUCT IMAGE
IN PROGRESS

High stability.

The sliding slip joint with double support ensures exceptional stability and a particularly long service life, even under high loads. The robust design guarantees reliable performance, even under demanding conditions.

Technical attributes.

Jaw opening max. (mm)	24 mm
Length mm (L)	175 mm
Physical length [mm]	177 mm
Header	black lacquered, jaws polished
Handles	black lacquered, box frame polished, plastic-coated with sure-grip surface
DIN	DIN ISO 8976
Alloy	Chrome Vanadium Steel
Opening width adjustment	6x

Logistics data.

Product no.	65516175
GTIN	4018754206353
Weight (g)	173 g
Volume (packaged, dm3)	0.06125 dm3
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82032000
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	175
Width mm (IFS)	35
Height mm (IFS)	10
Weight (gross, kg)	0,173
Weight PAP (kg)	0,000
Weight PVC (kg)	0,005

Length (packaged, mm) 175

Width (packaged, mm) 35

Height (packaging, mm) 10

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal