



VDE electrician's slotted screwdrivers DRALL+

4660 VDE

Product no. **46603080**
GTIN **4018754279050**
Model **DRALL+ 4660 VDE 8**



Label. VDE electrician's slotted screwdriver DRALL+ 1,2mm x 8mm L.175mm

Properties.

- for slotted screws
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- gunmetal finished blade tip
- 3-component handle with laser marking
- Chrome Alloy Steel



Product highlights.



Outstanding craftsmanship.

The blades are made of exceptionally fine industrial-grade chrome alloy steel, through-hardened and anchored in the grip in such a way that they stay there.

Robust.

Whether slotted or cross-head - the rough blade tips transfer even the greatest torques to the screws - precisely and safely.



Technologies and features.



3-component handle

Our 3-component handle combines hard and soft components, which give it its optimised ergonomics, maximum power transmission, and increased safety during daily use.



VDE DRALL+

Our VDE-DRALL+ handle is insulated to 1,000 V according to DIN EN 60900. It is non-slip and ergonomically shaped. An extended grip zone protects the fingers and a hand stop prevents the tool from accidentally slipping or rolling away.

Technical drawing.



Technical attributes.

Size	7
L1	175 mm
L2	300 mm
Width mm (b)	8 mm
a	1,2 mm
Drive profile	slotted
DIN	DIN EN 60900

Logistics data.

Product no.	46603080
GTIN	4018754279050
Weight (g)	170 g
Volume (packaged, dm3)	2.87615 dm3
Packing standard	10
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82054000
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	301
Width mm (IFS)	35
Height mm (IFS)	35
Weight (gross, kg)	1,800
Weight PAP (kg)	0,137

Weight PVC (kg)	0,000
Length (packaged, mm)	305
Width (packaged, mm)	115
Height (packaging, mm)	82

GTIN.



Images.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal