



Bolt cutters LightCUT®

980LC



Product no. **87980050**
GTIN **4005887009876**
Model **LightCUT® 980LC 800**



Label.

Bolt cutters LightCUT® 48HRC L.800mm

Properties.

- flat-oval, sturdy aluminium tubes ensure low weight
- for cutting up to 48 HRC
- cutter head made of wear-resistant special steel, drop-forged
- precise and simple adjustment of the cutting heads using eccentric screws
- optimised geometry reduces the effort required for cutting
- limit stop with extra-large buffer zone
- high-quality hardened and tempered for excellent wear resistance
- with 2-component handles

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Infinitely adjustable.

The sturdy, flat oval aluminium tubes make the bolt cutter particularly light, weighing about half as much without compromising the necessary stability. Heavy cabling, round bars, steel, reinforcing steel mesh, steel mesh, chain-link fences or chains up to 48 HRC can be cut effortlessly, powerfully and without fatigue, even during longer periods of use.



PRODUCT IMAGE
IN PROGRESS

Low wear and long service life.

The blades are made of inductively hardened, drop-forged special steel. These particularly low-wear blades remain reliably sharp even with intensive use. Thanks to the eccentric screws, the knives can be easily adjusted at any time, ensuring that the cutting performance remains clean and precise at all times. The bolt cutter itself is high-quality, hardened and tempered for excellent wear resistance.



PRODUCT IMAGE
IN PROGRESS

Maximum cutting capacity.

Our bolt cutter impresses with its high cutting capacity and low effort: the combination of an optimally coordinated cutting angle and transmission ratio makes cutting thick or hard bolts particularly easy. The stop with an extra-large buffer zone acts as a shock absorber, protects the tool and increases safety when working.



PRODUCT IMAGE
IN PROGRESS

Safe handling.

The non-slip, specially shaped 2-component handles fit securely and comfortably in the hand. They enable precise control of the tool, increase comfort when cutting and minimise the risk of slipping.

Technologies and features.



LightCUT

The flat-oval, high-strength aluminium tubes of the LightCUT range ensure a low weight, approximately half that of a comparable tool. For fatigue-free working and precise results.

Technical attributes.

Length mm (L)	800 mm
Length " (L)	32 "
Physical length [mm]	810 mm
Hardness	48 HRC
Cutting performance 19 HRC	10 mm
Cutting performance 40 HRC	8 mm
Cutting performance 48 HRC	7 mm

Logistics data.

Product no.	87980050
GTIN	4005887009876
Weight (g)	2650 g
Volume (packaged, dm ³)	5.103 dm ³
Packing standard	1
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82034000
Country of origin AWR	GERMANY
Region of origin	Thüringen
Depth mm (IFS)	810
Width mm (IFS)	210
Height mm (IFS)	30
Weight (gross, kg)	2,688
Weight PAP (kg)	0,000
Weight PVC (kg)	0,090

Length (packaged, mm)	810
Width (packaged, mm)	210
Height (packaging, mm)	30

GTIN.



Spare part(s), spare part(s) for.



87980100
Cutter head fastener
set



87980136
Cutter head with
screws