

## Double-ended ring spanners, external TORX®

### 21TX



Product no.	41251012
GTIN	4018754022359
Model	21TX E10 x E12 TORX®



#### Label.

Double-ended ring spanner E10 x E12 L.149.5mm

#### Properties.

- **differing** end sizes
- straight version
- for external TORX® screws
- durable, slim and lightweight design
- high flexural strength due to double-T profile
- STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
- drop-forged, hardened, and cooled in an oil bath
- Chrome Alloy Steel, chrome-plated

## Benefits.

High-quality double-ended ring spanner in straight version for high torque, without lateral tension; for external TORX® bolts.

The external TORX® profile transfers the force positively via the flanks of the lobes - for a secure fit and reduced risk of damage.

Made of robust Chrome Alloy Steel and additionally chrome-plated for high durability, reliable corrosion protection and enormous wear resistance.

A special manufacturing process enables thin-walled rings - slim for use in confined areas and at the same time robust enough for high loads.

The distinctive STAHLWILLE rounded finish gives the combination spanner a non-slip and comfortable feel for safe working, even with oily hands.

## Product highlights.



PRODUCT IMAGE  
IN PROGRESS

### Maximum force in a straight line.

Our straight double-ended ring spanners are used where screws and nuts are easily accessible and torque is important - for example, on flanges, brackets, frame constructions or machine units. The straight shape allows for clean, controlled application and direct power transmission - particularly practical for assembly and maintenance work when screw connections need to be loosened or tightened quickly and securely.



PRODUCT IMAGE  
IN PROGRESS

### Optimum power transmission.

Each spanner guarantees consistently excellent quality thanks to minimal manufacturing tolerances and high reproducible precision. The jaw and ring always fit securely on the screw, ensuring optimum power transmission.



PRODUCT IMAGE  
IN PROGRESS

### Non-slip surface.

STAHLWILLE spanners feature a high-quality, non-slip surface texture that enables safe working even with oily hands. The non-slip texture increases control during handling.



PRODUCT IMAGE  
IN PROGRESS

### High-quality workmanship.


The key is forged from high-quality Chrome Alloy Steel, which gives it high stability and resistance even in continuous use. It is also chrome-plated for corrosion resistance.

## Technologies and features.



### Double-T profile


Our ring, open-ended and combination spanners have an additional recess in the middle of the tool. Similar to the principle of a double-T beam, this provides a tremendous load capacity and maximum strength whilst reducing weight.



### Thin-walled rings

The thin-walled diameter of our rings makes it easier to work in confined spaces. The ring wall is deeper than standard nuts, which prevents jamming.

### Technical drawing.



### Technical attributes.

Size drive profile	E10 x E12
Length mm (L)	149,5 mm
a1	6,5 mm
a2	7,5 mm
Drive profile	TORX®
d1	13,7 mm
d2	15,7 mm
Alloy	Chrome Alloy Steel, chrom plated
Surface	chrome-plated

### Logistics data.

Product no.	41251012
GTIN	4018754022359
Weight (g)	33 g
Volume (packaged, dm3)	0.2125 dm3
Packing standard	10
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	150
Width mm (IFS)	16
Height mm (IFS)	8
Weight (gross, kg)	0,336
Weight PAP (kg)	0,000
Weight PVC (kg)	0,004
Length (packaged, mm)	170
Width (packaged, mm)	50
Height (packaging, mm)	25

**GTIN.**



**STAHLWILLE Eduard Wille GmbH**

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

[info@stahlwille.de](mailto:info@stahlwille.de) · [www.stahlwille.com](http://www.stahlwille.com)

© STAHLWILLE Eduard Wille GmbH, Wuppertal