

Pipe wrenches PowerGRIP

6573



Product no. **65735250**
GTIN **4018754206810**
Model **PowerGRIP 6573 250**

Label. Pipe wrench PowerGRIP L.250mm

- Properties.**
- smooth jaws to protect sensitive surfaces
 - secure grip when screwing, holding and bending
 - quick adjustment of the pipe wrench at the push of a button
 - for workpieces with parallel surfaces (nuts, screws, etc.)
 - variable and smooth fine adjustment
 - high transmission ratio for noticeable manual force amplification
 - with built-in protection against crush injuries
 - high-quality, hardened and tempered for excellent wear resistance
 - plastic coated handles

Benefits.

Sturdy pipe wrenches for gripping, holding, pressing and bending workpieces with flat surfaces (thin sheet metal, nuts, screws, etc.).

Use of the jaw stroke enables a "ratchet effect" for additional bolting function.

The pliers feature a non-slip plastic coating and built-in crush protection for improved ergonomics and safety.

Gentle bolting of sensitive fittings up to 36 mm thanks to smooth, parallel jaws without serration.

Infinitely variable and smooth-running quick adjustment at the push of a button on the tool.

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Practical ratchet effect.

The pipe wrench has a multifunctional design due to the special jaw stroke of the gripping jaws and thus also has a ratchet function.



PRODUCT IMAGE
IN PROGRESS

Precise fine adjustment.

Adaptation to the workpiece is achieved by precise, multi-stage quick adjustment of the pivot pin. Quick adjustment via push button makes the pipe wrench comfortable and flexible to use.



PRODUCT IMAGE
IN PROGRESS

Gentle application.

The full-surface and profile-free parallel jaws of this pipe wrench enable safe and gentle gripping of workpieces, such as sensitive fittings up to a diameter of 36 mm.



PRODUCT IMAGE
IN PROGRESS

Every action perfectly executed.

The ergonomically designed handles are coated with a non-slip plastic with a rough surface texture. This makes the pliers comfortable to hold and enables fatigue-free working - even with dirty hands. The integrated clamp protection reliably protects against crush injuries.



PRODUCT IMAGE
IN PROGRESS

High stability.

The sliding slip joint with double support ensures exceptional stability and a particularly long service life, even under high loads. The robust design guarantees reliable performance, even under demanding conditions.

Technical attributes.

Jaw opening max. (mm) 46 mm

Logistics data.

Product no. 65735250

Length mm (L)	250 mm	GTIN	4018754206810
Header	chrome-plated	Weight (g)	485 g
Handles	plastic overlay with a textured surface	Volume (packaged, dm3)	0.4186 dm3
Opening width adjustment	14x	Packing standard	1
		WEEE/ElektroG	nicht ear-pflichtig
		Customs tariff no.	82032000
		Country of origin AWR	GERMANY
		Region of origin	Nordrhein-Westfalen
		Depth mm (IFS)	260
		Width mm (IFS)	70
		Height mm (IFS)	23
		Weight (gross, kg)	0,485
		Weight PAP (kg)	0,000
		Weight PVC (kg)	0,006
		Length (packaged, mm)	260
		Width (packaged, mm)	70
		Height (packaging, mm)	23

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal