

## Electromechanical angle-controlled torque wrenches MANOSKOP®

### 714R/80 eClick



Product no.	<b>96501080</b>
GTIN	<b>4018754212798</b>
Model	<b>MANOSKOP® 714R/80 eClick</b>



#### Label.

Electromechanical angle-controlled torque wrenches MANOSKOP® 714R/80 eClick  
80-800N·m 3/4" L. 1253mm

#### Properties.

- eClick - electromechanical click
- acoustic and visual clicking
- with reversible ratchet (sizes 1-4), fine-tooth reversible ratchet (sizes 6-65) or ratchet insert tool with push-through square drive (sizes 80-100)
- 4 measuring modes (torque, angle of rotation, torque with 'angle of rotation' monitoring variable, angle of rotation with 'torque' monitoring variable)
- high-resolution colour OLED display and side signal lights
- visual evaluation of the bolted joint: yellow light (pre-warning threshold reached), green light (within tolerance range), red light (measurement outside tolerance range)
- freely configurable menu structure
- battery cap/battery pack with bayonet connection
- optional: Li-ion battery no. 7195-2 and charger no. 7160
- 3 function modes: clicking (patented electromechanical click), peak hold (indicating mode with peak value display) and track (indicating mode with actual value display)
- micro USB interface for data communication
- optional Bluetooth Low Energy module (5.2) or WLAN module
- QuickRelease safety lock - switching system for insert tools
- data storage for up to 2,500 bolting processes, including date and time stamp
- up to 200 bolted joints in a maximum of 25 sequence diagrams can be programmed
- different tolerance limits can be set depending on the type of bolted joint
- fast and precise adjustment via the keyboard
- no unintentional adjustments thanks to password-protected keypad lock
- acoustic and visual signal warns of torque wrench overload and forced clicking in clockwise tightening mode
- automatic indication of the next calibration date, user-configurable by time interval and/or number of joints
- fully automatic calibration and adjustment with the perfectControl® calibration and adjustment system no. 7794-2 (torque) or 7794-3 (torque and angle of rotation) for reducing error influencing factors
- Units of measurement: N·m, ft·lb, in·lb

- automatic extension length correction: option of entering a deviating extension length to ensure the required target value is achieved
- ready for operation again immediately after release
- for a controlled tightening process. The insert tool must be turned in clicking mode
- torque and angle of rotation displays visible at the same time
- measurement regardless of the force application point (for sizes 1, 2, and 4)
- safe handling due to the ergonomically shaped 2-component handle (resistant to the most common oils, greases, fuels, brake fluids, and Skydrol)
- 3 certificates included (torque indicating/clicking in accordance with DIN EN ISO 6789-2:2017, angle of rotation based on VDI/VDE 2648-2)
- in sturdy plastic box (sizes 40-100 in steel box)
- registered design, patented
- supplied with SensoMaster 4 software, USB cable, 4 micro-batteries AAA/LR03, 1.5 V
- **angle of rotation display resolution 0.1°**
- **angle of rotation display accuracy  $\pm 1^\circ$ ,  $\pm 1$  digit to 100°, >100° at least 1%,  $\pm 1$  digit**
- **torque display resolution  $\leq 60$  N·m: 0.01 N·m; > 60 N·m: 0.1 N·m**
- **torque display accuracy  $\pm 2\%$ ,  $\pm 1$  digit**

## Benefits.

Torque and angle-controlled torque wrench for bolted joints in accordance with the torque, angle of rotation, torque with 'angle of rotation' monitoring variable and angle of rotation with 'torque' monitoring variable tightening methods.

Visual evaluation of the bolted joint.

Thanks to the combination of the patented electromechanical clicking type and the display and acoustic feedback, the wrench provides signalling with maximum optimisation.

With patented eClick technology (electromechanical click): accurate electronic measurement combined with the familiar mechanical click.

Simple documentation of the recorded measurements on the PC via the USB interface and via optional communication modules (Bluetooth LE or WLAN).

## Product highlights.



### Angle of rotation and torque measurement

Our torque and angle wrenches make it possible to tighten bolted joints in accordance with the torque, angle of rotation, torque with 'angle of rotation' monitoring variable and angle of rotation with 'torque' monitoring variable tightening method. Thanks to this functional diversity, the wrench is suitable for the most popular tightening methods.




### Electromechanical clicking type.

The MANOSKOP® with patented electromechanical release measures the applied torque electronically. A visual evaluation of the bolted connection is provided by a display and signal lights on the side. Unlike a purely electronic torque wrench, the cycle and haptic user feedback are also mechanical. A clearly perceptible cycle and an equally audible click indicate that the target value has been reached.



### Comprehensive documentation.

Comprehensive documentation. Our eClick torque wrenches are suitable for documentation purposes. They can be easily configured and programmed using the SensoMaster software. This means that all of the data can be read out, stored, and processed further on the PC for improved monitoring and optimisation of the work processes. Digital measurement also enables the tool to signal precisely when the target value is reached and allows the actually applied tightening torque (actual value) to be documented.



### Also suitable for difficult application areas.

STAHLWILLE electromechanical torque wrenches are ideal for application areas in which electronic torque wrenches are pushed to their signalling limits - such as when working overhead or if the display cannot be read off. Even in noisy, busy and very bright environments which can make it difficult to perceive vibrations or visual and acoustic signals, electromechanical torque wrenches use patented haptic feedback to indicate that the target value has been reached.



### More reliability.

Our electromechanical torque wrenches minimise operating errors. Screw joints and sequence plans, for example, can be parameterised and saved. The torque wrench then automatically sets the clicking type torque for the selected bolted joint. The clicking type torque is also specified digitally so that parallax effects (errors caused by to an incorrect reading angle), which are possible when using a mechanical scale are eliminated.



### Perfect entry level solution.

Electromechanical STAHLWILLE torque wrenches make it easier to switch from purely mechanical to documenting torque wrenches. Users who previously only worked with mechanical wrenches become accustomed to them more quickly because our electromechanical torque wrenches provide maximum optimised signalling with haptic, acoustic and visual feedback. This simplifies the switch to digital technology.

## Technologies and features.



### eClick.

The electromechanical eClick torque tools combine digital measuring technology with a mechanical click. This allows torques to be applied accurately, with the additional advantage of a clearly detectable, haptic stop signal. This helps users to achieve reliable, reproducible bolted joints without sacrificing the familiar handling of traditional tools.



### QuickRelease

The QuickRelease safety lock prevents unintentional loss of insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change. In transducers: The QuickRelease safety lock helps you to quickly mount and change transducers. The transducers lock into the calibration system and only unlock again at the push of the buttons.



### 2-component handle

Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.



### DIN EN ISO 6789-2

Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.

## Technical attributes.

Size	80
Anzeigeabweichung	Drehwinkel $\pm 1^\circ$ , $\pm 1$ Digit bis $100^\circ$ , $>100^\circ$ mindestens $1\%$ , $\pm 1$ Digit
Tool holder size [internal square]	22 x 28 mm
Measuring range N·m	80-800 N·m
Measuring range ft·lb	60-600 ft·lb
Measuring range in·lb	720-7200 in·lb
External square drive (inch)	3/4
Length mm (L)	1253 mm
Width mm (b)	130 mm
Height mm (h)	95 mm
Number of teeth	30
Battery type	Micro (AAA) 1,5V
DIN	DIN EN ISO 6789-2:2017
Weight with box	12300 g

## Logistics data.

Product no.	96501080
GTIN	4018754212798
Weight (g)	6487 g
Volume (packaged, dm <sup>3</sup> )	18.8955 dm <sup>3</sup>
Packing standard	1
WEEE/ElektroG	Großgeräte B2C
Customs tariff no.	82041100
Country of origin AWR	GERMANY
Region of origin	Nordrhein-Westfalen
Depth mm (IFS)	1530
Width mm (IFS)	130
Height mm (IFS)	95
Weight (gross, kg)	11,800
Weight PAP (kg)	0,650
Weight PVC (kg)	0,000
Length (packaged, mm)	1530
Width (packaged, mm)	130
Height (packaging, mm)	95

## Parts list.



51110057  
USB cable



59220003  
Battery

## GTIN.



## Accessories (for).



96521161  
Interface adaptor set




52110061  
Interface adaptor



52110062  
Docking station for  
No. 714



52110162  
Support for docking  
station No. 7762



96585235  
SensoMaster software  
license



54101195  
Li-Ion battery



52110220  
Bluetooth Low Energy  
module

**STAHLWILLE Eduard Wille GmbH**

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal