

Torque wrenches Series MANOSKOP®

755



Product no. **50010004**
GTIN **4018754031603**
Model **755/4**

Label. MANOSKOP® torque wrench 755 4-40N·m 9 x 12 mm L. 201 mm

Properties.

- clicking type with dual stop signal
- for work on assembly lines or for repetitive production tasks.
- no adjustment scale; therefore adjustment with test equipment is required, e.g. with the STAHLWILLE test devices No. 7707 W, SmartCheck or the perfectControl® calibration system No. 7794, or calibration systems No. 7706. 7791)
- with holder for interchangeable insert tools
- particularly slim design
- handle and shaft made of square steel pipe
- Further loading after clicking or loads in the opposite direction of operation (up to the max. measurement range of the torque wrench) do not affect the trigger mechanism, which protects it from damage
- counter-clockwise tightening by turning the insert tool over
- can be supplied pre-set at defined torque value and with certification (additional charge applies)
- **accuracy ± 4%**

Technical drawing.



Technical attributes.

Size **4**

Logistics data.

Product no. **50010004**

Anzeigeabweichung	± 4 %	GTIN	4018754031603
Tool holder size [internal square]	9 x 12 mm	Weight (g)	500 g
Measuring range N·m	4-40 N·m	Volume (packaged, dm³)	0.74727 dm ³
Measuring range ft·lb	3-30 ft·lb	Packing standard	1
MA N·m	4 N·m	WEEE/ElektroG	nicht ear-pflichtig
Nominal value N·m	40 N·m	Customs tariff no.	82041100
Length mm (L)	201 mm	Country of origin AWR	GERMANY
Width mm (b)	22 mm	Region of origin	Nordrhein-Westfalen
Height mm (h)	18 mm	Depth mm (IFS)	202
LF	172 mm	Width mm (IFS)	37
SF	17,5 mm	Height mm (IFS)	28
		Weight (gross, kg)	0,510
		Weight PAP (kg)	0,000
		Weight PVC (kg)	0,066
		Length (packaged, mm)	230
		Width (packaged, mm)	57
		Height (packaging, mm)	57

GTIN.



STAHLWILLE Eduard Wille GmbH

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0

info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH, Wuppertal